

SITOP POWER/1AC/24VDC/5A/FLAT DESIGN
 SITOP power 5 A, Special Line Stabilized power supply input:
 120/230 V AC, output: 24 V DC/5 A



Input	
Input	1-phase AC
<ul style="list-style-type: none"> Note 	Set by means of selector switch on the device
supply voltage	
<ul style="list-style-type: none"> 1 at AC rated value 2 at AC rated value 	120 V 230 V
input voltage	
<ul style="list-style-type: none"> 1 at AC 2 at AC 	85 ... 132 V 170 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering	at $V_{in} = 93/187$ V
Mains buffering at lout rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> at rated input voltage 120 V at rated input voltage 230 V 	2.2 A 1.2 A

Switch-on current limiting (+25 °C), max.	32 A
duration of inrush current limiting at 25 °C	
• maximum	3 ms
I ² t, max.	0.8 A ² ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 6 A characteristic C

Output

Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	1 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	150 mV
Residual ripple peak-peak, typ.	40 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	100 mV
Adjustment range	22 ... 29 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
On/off behavior	No overshoot of V _{out} (soft start)
Startup delay, max.	2 s
Voltage rise, typ.	40 ms
Rated current value I _{out} rated	5 A
Current range	0 ... 5 A
supplied active power typical	120 W
short-term overload current	
• on short-circuiting during the start-up typical	20 A
• at short-circuit during operation typical	20 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	500 ms
• at short-circuit during operation	500 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at V _{out} rated, I _{out} rated, approx.	88 %
Power loss at V _{out} rated, I _{out} rated, approx.	17 W

Closed-loop control

Dynamic mains compensation (V _{in} rated ±15 %), max.	0.3 %
--	-------

Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ.	0.5 %
Load step setting time 50 to 100%, typ.	0.1 ms
Load step setting time 100 to 50%, typ.	0.1 ms

Protection and monitoring

Output overvoltage protection	Additional control loop, shutdown at approx. 33 V, automatic restart
Current limitation	5.5 ... 6.5 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current RMS value <ul style="list-style-type: none"> • maximum 	5 A
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
leakage current <ul style="list-style-type: none"> • maximum • typical 	3.5 mA 0.26 mA
Degree of protection (EN 60529)	IP20

Approvals

CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	-
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	No
Marine approval	-

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	-
Noise immunity	EN 61000-6-2

environmental conditions

ambient temperature <ul style="list-style-type: none"> • during operation <ul style="list-style-type: none"> — Note • during transport • during storage 	0 ... 60 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics	
Connection technology	screw-type terminals
Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
• Output	L+, M: 3 screw terminals each for 0.5 ... 2.5 mm ²
• Auxiliary	-
width of the enclosure	160 mm
height of the enclosure	130 mm
depth of the enclosure	60 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Weight, approx.	0.6 kg
product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	1 250 000 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)