

SITOR fuse link, with blade contacts, NH00, In: 35 A, gR, Un AC: 690 V, Un DC: 440 V, front indicator



| Model | |
|--|------------------------------------|
| product brand name | SENTRON |
| product designation | SITOR fuse link |
| design of the product | With blade contacts |
| design of an identification indicator | front indicator |
| design of the switching contact | With blade contacts, silver-plated |
| design of the fuse link | SITOR, LV HRC design |
| General technical data | |
| size of fuse system / acc. to DIN EN 60269-1 | NH00 |
| operating class of the fuse link | gR |
| varying load factor (WL) | 0.95 |
| Supply voltage | |
| type of voltage | AC/DC |
| operational current / at AC / rated value | 35 A |
| supply voltage | |
| • at AC / rated value | 690 V |
| • at DC | 440 V |
| Switching capacity | |

| | |
|---|--------|
| switching capacity current | |
| <ul style="list-style-type: none"> • acc. to IEC 60947-2 / rated value | 100 kA |

Dissipation

| | |
|--|-----|
| power loss [W] | 9 W |
| power loss [W] | |
| <ul style="list-style-type: none"> • for rated value of the current / at AC / in hot operating state / per pole | 9 W |
| <ul style="list-style-type: none"> • maximum | 9 W |

Product details

| | |
|---------------------|-------------------------|
| product description | Not non-interchangeable |
|---------------------|-------------------------|

Mechanical Design

| | |
|-------------------|--------------------------|
| mounting position | Any, preferably vertical |
| net weight | 203 g |

Environmental conditions

| | |
|---|-------------------------------------|
| ambient temperature | |
| <ul style="list-style-type: none"> • minimum | -20 °C |
| <ul style="list-style-type: none"> • maximum | 50 °C |
| environmental category | -20 to +50 at 95% relative humidity |

Certificates

| | |
|--|---|
| reference code | |
| <ul style="list-style-type: none"> • acc. to DIN EN 61346-2 | F |
| <ul style="list-style-type: none"> • acc. to IEC 81346-2 | F |

| General Product Approval | Declaration of Conformity | Test Certificates | other |
|--|---|--|---|
|  CCC |  UR |  EAC |  EG-Konf. |
| | | Special Test Certificate | Miscellaneous |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE8003-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NE8003-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE8003-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



