



SIMATIC ET 200SP, BaseUnit BU20-P12+A0+0B, BU type D0, Push-in terminals, without AUX terminals, bridged to the left, WxH: 20 mmx117 mm

General information	
Product type designation	BU type D0
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>For P1 and P2 bus</li> <li>For AUX bus</li> </ul>	120 V 120 V; Equal potential group to P1/P2 bus or PE
Rated value (AC)	
<ul style="list-style-type: none"> <li>For P1 and P2 bus</li> <li>For AUX bus</li> <li>for process terminals</li> </ul>	277 V 277 V; Equal potential group to P1/P2 bus or PE 277 V; 480 V (L1 - L2 - L3); 277 V (L, N)
Mains filter	
<ul style="list-style-type: none"> <li>integrated</li> </ul>	Yes; Between N and FE
Current carrying capacity	
up to 60 °C, max.	5 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	5 A
Hardware configuration	
Automatic encoding	Yes
Formation of potential groups	
<ul style="list-style-type: none"> <li>New potential group</li> <li>Potential group continued from the left</li> </ul>	No Yes
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1; Type D0
Potential separation	
between backplane bus and supply voltage	Yes
between power bus and supply voltage	Yes
Isolation	
Isolation tested with	3 100 V DC
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-30 °C 60 °C -30 °C 50 °C
Altitude during operation relating to sea level	

- Installation altitude above sea level, max.

2 000 m; On request: Installation altitudes greater than 2 000 m

#### Accessories

##### Color coding labels

- for process terminals does not exist
- for AUX terminals does not exist
- for add-on terminals does not exist

#### Connection method

##### Terminals

- Terminal type Push-in terminal
- Conductor cross-section, min. 0.14 mm<sup>2</sup>
- Conductor cross-section, max. 2.5 mm<sup>2</sup>
- Number of process terminals to I/O module 12; Pro slot
- Number of terminals to AUX bus 0
- Number of add-on terminals 0
- Number of terminals with connection to P1 and P2 bus 0; Pro slot

#### Dimensions

Width	20 mm
Height	117 mm
Depth	35 mm

#### Weights

Weight, approx.	47 g
-----------------	------

**last modified:** 3/23/2020 