

RC unit for 5SL4, 3-pole, type AC, In: 63 A, 300 mA, Un AC: 400 V



Model	
product brand name	SETRON
product designation	RC unit
design of the product	Instantaneous
product variations	for 5SL4
General technical data	
number of poles	3
size of installation devices / acc. to DIN 43880	1
mechanical service life (switching cycles) / typical	10 000
switching function / short-term delayed	No
overvoltage category	III
insulation voltage / rated value	460 V
Supply voltage	
operational current / at AC / rated value	63 A
supply voltage	
• at AC / rated value	230/400 V
• for testing equipment / minimum	195 V
operating frequency	50 Hz
supply voltage frequency / rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Dissipation	
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	3 W
• maximum	9 W
Current	
tripping fault current / rated value	300 mA
residual current type	AC
operational current	
• at 40 °C / rated value	58.59 A
• at 45 °C / rated value	58.59 A
• at 50 °C / rated value	56.7 A
• at 55 °C / rated value	54.81 A
• at 60 °C / rated value	53.55 A
• at 65 °C / rated value	52.29 A
• at 70 °C / rated value	50.4 A

Product details	
product feature / silicon-free	Yes
product extension / installable / supplementary devices	Yes
Connections	
connectable conductor cross-section / solid	
• minimum	1.5 mm <sup>2</sup>
• maximum	25 mm <sup>2</sup>
connectable conductor cross-section / stranded	
• minimum	1.5 mm <sup>2</sup>
• maximum	25 mm <sup>2</sup>
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
position / of power supply cord	top or bottom
Mechanical Design	
height	90 mm
width	105 mm
depth	70 mm
installation depth	70 mm
number of modular width units	3
fastening method	DIN rail (REG)
mounting position	any
net weight	320 g
Environmental conditions	
ambient temperature / during operation	
• minimum	-5 °C
• maximum	45 °C
ambient temperature / during storage	
• minimum permissible	-40 °C
• maximum permissible	75 °C
number of test cycles / for environmental testing / acc. to IEC 60068-2-30	28
<b>General Product Approval</b>	<b>Declaration of Conformity</b>



[Miscellaneous](#)



Declaration of Conformity

other

Dangerous Good



[Miscellaneous](#)

[Transport Information](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SM2636-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SM2636-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SM2636-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2636-0)

Tender specifications

