

Spare part Push Button Panel PP17 II 32 short-stroke keys, 32 surface LEDs, 16 DI and 16 DO terminals PROFIBUS DP12

General information	
Product type designation	PP17-II
Control elements	
With parameterizable keys	Yes
Keyboard fonts	
<ul style="list-style-type: none"> • Membrane keyboard <ul style="list-style-type: none"> — user-definable label membrane keys • Short-stroke keys <ul style="list-style-type: none"> — Number of short-stroke keys 	Yes 32
Expansions for operator control of the process	
<ul style="list-style-type: none"> • DP direct LEDs (LEDs as S7 output I/O) • Number of color modes for LED • Direct keys (keys as S7 input I/O) 	32 3 32
Installation type/mounting	
Mounting type	Clamp terminals
Mounting position	vertical
Rack mounting	No
Front mounting	Yes
Rail mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	No
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	35°
Number of slots for command devices and signaling units	0
Supply voltage	
Type of supply voltage	DC
permissible range, lower limit (DC)	18 V
permissible range, upper limit (DC)	30 V
Input current	
Starting current inrush I _t	0.03 A ² ·s
Type of output	
LED colors	red, yellow, green
<ul style="list-style-type: none"> • red • yellow • green • white • blue 	Yes Yes Yes No No
Digital inputs	
Number of digital inputs	16
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
Digital outputs	
Number of digital outputs	16
<ul style="list-style-type: none"> • in groups of 	4
Short-circuit protection	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • with resistive load, max. 	100 mA

<ul style="list-style-type: none"> with inductive load, max. on lamp load, max. 	100 mA; max. 2 watts 2 W
Output voltage	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
Total current of the outputs	
<ul style="list-style-type: none"> Current per channel, max. Current per group, max. 	100 mA 500 mA
Interfaces	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Industrial Ethernet	
<ul style="list-style-type: none"> Industrial Ethernet status LED Number of ports of the integrated switch 	0 0
Protocols	
PROFINET	No
Supports protocol for PROFINET IO	No
PROFINET CBA	No
IRT	No
PROFIsafe	No
PROFIBUS	Yes
MPI	Yes
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
<ul style="list-style-type: none"> TCP/IP 	No
Redundancy mode	
Media redundancy	
— MRP	No
Further protocols	
<ul style="list-style-type: none"> AS-Interface Safety at Work CAN Data-Highway DeviceNet DeviceNet Safety EtherNet/IP Foundation Fieldbus INTERBUS INTERBUS-Safety Local Operating Network MODBUS SafetyBUS p SERCOS SUCOnet other bus systems 	No No No No No No No No No No No No No No No No
Test commissioning functions	
Illuminant test	Yes
Key and signal lamp test	Yes; automatically when switching on
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> Limit class A, for use in industrial areas Limit class B, for use in residential areas 	Yes No
Degree and class of protection	
NEMA (front)	
<ul style="list-style-type: none"> Enclosure Type 4 at the front Enclosure Type 4x at the front 	No No
Standards, approvals, certificates	
CE mark	Yes

cULus	No
RCM (formerly C-TICK)	Yes
KC approval	No
Suitable for safety functions	No
Use in hazardous areas	
• ATEX Zone 2	No
• ATEX Zone 22	No
• cULus Class I Zone 1	No
• cULus Class I Zone 2, Division 2	No
• FM Class I Division 2	No
Marine approval	
• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
• Polski Rejestr Statkow (PRS)	No
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
• Operation (vertical installation)	0 °C up to 55 °C
— For vertical installation, min.	0 °C
— For vertical installation, max.	55 °C
• Operation (max. tilt angle)	0 °C up to 55 °C
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %
Configuration	
Configuration software	
• STEP 7 Basic (TIA Portal)	Yes
• STEP 7 Professional (TIA Portal)	Yes
Functionality under WinCC (TIA Portal)	
Process coupling	
• S7-1200	Yes
• S7-1500	Yes
• S7-200	No
• S7-300/400	Yes
• LOGO!	No
• WinAC	Yes
• SINUMERIK	No
• SIMOTION	No
• Allen Bradley (EtherNet/IP)	No
• Allen Bradley (DF1)	No
• Mitsubishi (MC TCP/IP)	No
• Mitsubishi (FX)	No
• OMRON (FINS TCP)	No
• OMRON (LINK/Multilink)	No
• Modicon (Modbus TCP/IP)	No
• Modicon (Modbus)	No
Mechanics/material	
Service life	
• Short-stroke keys (in switching cycles)	1 500 000

- LEDs (ON period)

100 %

Dimensions

Width of the housing front	240 mm
Height of housing front	204 mm
Mounting cutout, width	226 mm
Mounting cutout, height	190 mm
Overall depth	53 mm

Weights

Weight without packaging	1 130 g
--------------------------	---------

last modified:

1/16/2021 