Product data sheet Characteristics

ZC2JE015

Limit switch head, Limit switches XC Standard, ZC2J, without lever left and right actuation, +120 °C





Main

| IVIAIII | | |
|-----------------------------------|---|--|
| Range of product | OsiSense XC | |
| Series name | Special format | |
| Product or component type | Limit switch head | |
| Device short name | ZC2J | |
| Head type | Rotary head | |
| Product compatibility | XC2J | |
| Associated lever Associated body | ZC2JY12 ZC2JY51 ZC2JY31 ZC2JY91 ZC2JY13 ZC2JY13 ZC2JY11 ZC2JY81 ZC2JY81 | |
| Associated body | ZC2JC25 | |
| Movement of operating head | Rotary | |
| Type of operator | Without operating lever spring return | |
| Type of approach | Lateral approach, 2 directions | |
| | | |

Complementary

| Switch actuation | From left and right CW and CCW | |
|------------------|--------------------------------|--|
| Positive opening | Without | |
| Net weight | 0.21 kg | |
| Head material | Metal | |

Environment

| Ambient air temperature for operation | 10120 °C |
|---------------------------------------|------------------|
| Ambient air temperature for storage | 10120 °C |
| Environmental characteristic | High temperature |

Packing Units

| • | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 231 g |
| Package 1 Height | 5 cm |
| Package 1 width | 5 cm |
| Package 1 Length | 9.5 cm |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 16 |
| Package 2 Weight | 3.921 kg |
| Package 2 Height | 15 cm |
| Package 2 width | 15 cm |
| Package 2 Length | 40 cm |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--|--|
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| | | |

Contractual warranty

| Warranty 18 months |
|--------------------|
|--------------------|