



Main

| | |
|---------------------------|--------------|
| Product name | UA |
| Product or component type | Control unit |

Complementary

| | |
|---|---|
| [Us] rated supply voltage | 220...240 V AC at 50/60 Hz |
| Operating mode | Forced operation on replacement source Stop (both normal and replacement source off) Automatic operation Forced operation on normal source |
| Interlocked device | Masterpact NW Compact NS100...630 Compact NS630b...1600 Masterpact NT |
| Selection modes | Circuit breaker on R Circuit breaker on N |
| Genset exerciser | Startup control Adjustable delayed shutdown |
| Test function | By pressing the test button on the front of the controller |
| Complementary function | Selection of type of normal source (single-phase or three-phase) Setting of maximum startup time for the replacement source Voluntary transfer to replacement source (e.g. energy management commands) Forced normal source if replacement source not operational during peak-tariff Additional contact: transfer to replacement source only if contact is closed |
| Local signalling | Fault trip On Off |
| Input type | Contacts customer voluntary order to transfer to source R |
| Output type | Contacts customer: indication of operation in automatic or stop mode |
| [Ith] conventional free air thermal current | 8 A |
| [Ie] rated operational current | AC-12: 4 A AC 440 V |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|-------------------------|--|
| Standards | IEC 947-5-1 |
| IP degree of protection | IP20 connectors: conforming to EN 60529 IP40 front: conforming to EN 60529 IP30 side: conforming to EN 60529 |
| IK degree of protection | Front: IK07 conforming to EN 50102 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.586 kg |
| Package 1 Height | 15.5 cm |
| Package 1 width | 16 cm |
| Package 1 Length | 18 cm |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 10.697 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 40 cm |
| Package 2 Length | 60 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|