

XLP00-6M8



Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

General Information

Extended Product Type:	XLP00-6M8
Product ID:	1SEP101890R0004
EAN:	7025840021186
Catalog Description:	XLP00-6M8 Fuse Switch Disconnecter
Long Description:	XLP00,3-pole,160A, incl. 6 x M8x16mm bolts

Ordering

EAN:	7025840021186
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Width:	105 mm
Product Net Height:	187 mm
Product Net Depth:	90 mm
Product Net Weight:	0.63 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 1 Height:	187 mm
Package Level 1 Length:	90 mm
Package Level 1 Gross Weight:	0.63 kg
Package Level 2 EAN:	7025840021186

Additional Information

Degree of Protection:	IP30
Frequency (f):	MainCircuit 50/60 Hz
Fuse Size:	NH00 NH000
Fuse System:	DIN
Fuse Type:	NH
Fuse Protected Short-Circuit Making:	MainCircuit 50 kiloampere rms

Fuse Protected Short-Circuit Withstand:	MainCircuit 50 kiloampere rms
Handle Type:	Front cover 3P
Mounting Type:	Baseplate
Number of Poles:	3
Order Multiple:	1 piece
Product Main Type:	XLP00
Product Name:	Fuse Switch Disconnecter
Rated Current (I_n):	160 A
Rated Frequency (f):	Main Circuit 50/60 Hz
Rated Voltage (U_r):	400 V AC 500 V AC 690 V AC
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Operational Current AC-21B (I_e):	(690 V) 125 A
Rated Operational Current AC-22B (I_e):	(500 V) 160 A
Rated Operational Current AC-23B (I_e):	(400V) 125 A
Rated Operational Voltage:	400 V AC 500 V AC 690 V AC
Special Functions:	Not Included
Suitable For:	Baseplate
Terminal Type:	Bolt

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SEC312012D0201
Declaration of Conformity - CE:	1SEP500050P0001

Classifications

ETIM 4:	EC001040 - Fuse switch disconnecter
ETIM 5:	EC001040 - Fuse switch disconnecter
ETIM 6:	EC001040 - Fuse switch disconnecter
Object Classification Code:	S

