

XLP1-6M10



Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

General Information

| | |
|-------------------------------|---------------------------------------|
| Extended Product Type: | XLP1-6M10 |
| Product ID: | 1SEP101891R0004 |
| EAN: | 7025840020325 |
| Catalog Description: | XLP1-6M10 Fuse Switch Disconnecter |
| Long Description: | XLP1,3-pole,250A, incl. 6 x M10 bolts |

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 7025840020325 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85389099 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width: | 185 mm |
| Product Net Height: | 270 mm |
| Product Net Depth: | 116 mm |
| Product Net Weight: | 1.8 kg |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 185 mm |
| Package Level 1 Height: | 270 mm |
| Package Level 1 Length: | 116 mm |
| Package Level 1 Gross Weight: | 1.8 kg |
| Package Level 2 EAN: | 7025840020325 |

Additional Information

| | |
|--|-------------------------------|
| Degree of Protection: | IP30 |
| Frequency (f): | MainCircuit 50/60 Hz |
| Fuse Size: | NH1 |
| Fuse System: | DIN |
| Fuse Type: | NH |
| Fuse Protected Short-Circuit Making: | MainCircuit 50 kiloampere rms |
| Fuse Protected Short-Circuit Withstand: | MainCircuit 50 kiloampere rms |

| | |
|---|----------------------------------|
| Handle Type: | Front cover 3P |
| Mounting Type: | Baseplate |
| Number of Poles: | 3 |
| Order Multiple: | 1 piece |
| Product Main Type: | XLP1 |
| Product Name: | Fuse Switch Disconnecter |
| Rated Current (I_n): | 250 A |
| Rated Frequency (f): | Main Circuit 50/60 Hz |
| Rated Voltage (U_r): | 500 V AC 690 V AC 800 V AC |
| Rated Impulse Withstand Voltage (U_{imp}): | Main Circuit 8 kV |
| Rated Operational Current AC-21B (I_e): | (690 V) 200 A |
| Rated Operational Current AC-22B (I_e): | (500 V) 250 A |
| Rated Operational Voltage: | 500 V AC 690 V AC 800 V AC |
| Special Functions: | Not Included |
| Suitable For: | Baseplate |
| Terminal Type: | Bolt |

Certificates and Declarations (Document Number)

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SEC312012D0201 |
| Declaration of Conformity - CE: | 1SEP500050P0001 |

Classifications

| | |
|------------------------------------|-------------------------------------|
| ETIM 4: | EC001040 - Fuse switch disconnecter |
| ETIM 5: | EC001040 - Fuse switch disconnecter |
| ETIM 6: | EC001040 - Fuse switch disconnecter |
| Object Classification Code: | S |

