

XLP1-A60/85-B-3BC-below



Products → Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

General Information

Extended Product Type:	XLP1-A60/85-B-3BC-below
Product ID:	1SEP101918R0001
EAN:	7025840019664
Catalog Description:	XLP1-A60/85-B-3BC-below Fuse Switch Disconnecter
Long Description:	XLP1,3-pole,250A, incl. A60/85 adapter and 3 Bridge Clamps, cable below

Ordering

EAN:	7025840019664
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Width:	185 mm
Product Net Height:	292 mm
Product Net Depth:	160 mm
Product Net Weight:	2.47 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	185 mm
Package Level 1 Height:	292 mm
Package Level 1 Length:	160 mm
Package Level 1 Gross Weight:	2.47 kg
Package Level 2 EAN:	7025840019664

Additional Information

Degree of Protection:	IP30
Frequency (f):	MainCircuit 50/60 Hz
Fuse Size:	NH1
Fuse System:	DIN
Fuse Type:	NH
Fuse Protected Short-Circuit Making:	MainCircuit 50 kiloampere rms
Fuse Protected Short-Circuit Withstand:	MainCircuit 50 kiloampere rms

Handle Type:	Front cover 3P
Mounting Type:	60mm Busbar System
Number of Poles:	3
Order Multiple:	1 piece
Product Main Type:	XLP1
Product Name:	Fuse Switch Disconnecter
Rated Current (I_n):	250 A
Rated Frequency (f):	Main Circuit 50/60 Hz
Rated Voltage (U_r):	500 V AC 690 V AC 800 V AC
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Operational Current AC-21B (I_e):	(690 V) 200 A
Rated Operational Current AC-22B (I_e):	(500 V) 250 A
Rated Operational Voltage:	500 V AC 690 V AC 800 V AC
Special Functions:	Not Included
Suitable For:	60mm Busbar System
Terminal Type:	Cable Clamp

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SEC312012D0201
Declaration of Conformity - CE:	1SEP500050P0001

Classifications

ETIM 4:	EC001040 - Fuse switch disconnecter
ETIM 5:	EC001040 - Fuse switch disconnecter
ETIM 6:	EC001040 - Fuse switch disconnecter
Object Classification Code:	S
UNSPSC:	39121600

