OC10G01PNBN00NA1

Current:



Products + Low Voltage Products and Systems + Switches + Cam Switches

| General Information | |
|--|--|
| Extended Product Type: | OC10G01PNBN00NA1 |
| Product ID: | 1SCA126421R1001 |
| EAN: | 6417019563848 |
| Catalog Description: | OC10G01PNBN00NA1 Cam switch |
| Long Description: | OC10 Cam switch, Ith=10A, ON-OFF, 1-contact, Snap-on door mounting, B |
| | lack Basic handle. Black handle and frontplate with standard text are includ |
| | ed. Special engraved frontplates to be ordered as separate items. |
| Ordering | |
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85365080 |
| Popular Downloads | |
| Data Sheet, Technical Information | : 1SCC302009C0201 |
| Instructions and Manuals: | 1SCC302013F0006 |
| Wiring Diagram: | 1SCC302014M0201 |
| Dimensions | |
| Product Net Width: | 32 mm |
| Product Net Height: | 32 mm |
| Product Net Depth: | 69 mm |
| Product Net Weight: | 0.04 kg |
| Technical | |
| Rated Operational Current AC-22A (I _e): | (500 V) 10 A |
| Rated Operational Current AC-23A (I _e): | (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A |
| Rated Operational Power AC-23A (P _e): | (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW |
| Conventional Free-air Thermal Current (I _{th}): | q = 40 °C 10 A |
| Conventional Thermal Current (I _{the}): | Fully Enclosed 10 A |
| Rated Continuous Thermal | 10 A |

| Rated Impulse Withstand Voltage (U _{imp}): | 2.5 kV |
|---|---|
| Rated Insulation Voltage (U _i): | 500 V |
| Rated Operational Voltage: | 500 V |
| Rated Short-time Withstand Current (I _{cw}): | for 1 s 0.12 kiloampere rms |
| Power Loss: | 0.6 W |
| Pollution Degree: | 3 |
| Handle Type: | Basic handle |
| Special Functions: | ON - OFF switch: 0-position: 9 o´clock, step angle 90°, front plate 0-1 |
| Color: | Black |
| Mounting Type: | Snap-on door mounting |
| Number of Contacts: | 1 |
| Number of Poles: | 1 |
| Terminal Type: | Screw Terminals |
| Technical UL/CSA | |
| Ampere Rating UL/CSA: | 600 V AC 10 A |
| Certificates and Declarations (| Document Number) |
| Declaration of Conformity - CE: | 1SCC302005D0201 |
| Instructions and Manuals: | 1SCC302013F0006 |
| | |
| Container Information | |
| Container Information Package Level 1 Units: | 1 piece |
| | 1 piece 50 mm |
| Package Level 1 Units: | |
| Package Level 1 Units: Package Level 1 Width: | 50 mm |
| Package Level 1 Units: Package Level 1 Width: Package Level 1 Length: | 50 mm 108 mm |
| Package Level 1 Units: Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: | 50 mm 108 mm 50 mm |
| Package Level 1 Units: Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight: | 50 mm 108 mm 50 mm 0.04 kg |
| Package Level 1 Units: Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight: Package Level 1 EAN: | 50 mm 108 mm 50 mm 0.04 kg |
| Package Level 1 Units:Package Level 1 Width:Package Level 1 Length:Package Level 1 Height:Package Level 1 Gross Weight:Package Level 1 EAN:Classifications | 50 mm 108 mm 50 mm 0.04 kg 6417019563848 |
| Package Level 1 Units: Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight: Package Level 1 EAN: Classifications Object Classification Code: | 50 mm 108 mm 50 mm 0.04 kg 6417019563848 |

