OC25G03KNBN00NA3



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information	
Extended Product Type:	OC25G03KNBN00NA3
Product ID:	1SCA126444R1001
EAN:	6417019564142
Catalog Description:	OC25G03KNBN00NA3 Cam switch
	OC25 Cam switch, Ith=25A, ON-OFF, 3-contacts, Snap-on door mounting, Black Key operated. Black handle and frontplate with standard text are incl uded. Special engraved frontplates to be ordered as separate items.
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080
Popular Downloads	
Data Sheet, Technical Information:	1SCC302009C0201
Instructions and Manuals:	1SCC302013F0006
Wiring Diagram:	1SCC302014M0201
Dimensions	
Product Net Width:	51 mm
Product Net Height:	51 mm
Product Net Depth:	77 mm
Product Net Weight:	0.13 kg
Technical	
Rated Operational Current AC-22A (I _e):	(500 V) 20 A (690 V) 20 A

('e)·	(090 V) 20 A
Rated Operational Current AC-23A	(690 V) Three Phase 5.9 A
(I _e):	(500 V) Three Phase 8.1 A
	(230 V) Three Phase 15 A
	(400 V) Three Phase 15 A
Rated Operational Power AC-23A	(690 V) Three Phase 4.8 kW
(P _e):	(500 V) Three Phase 4.8 kW
	(230 V) Three Phase 2.6 kW
	(400 V) Three Phase 7.5 kW
Conventional Free-air Thermal	q = 40 °C 25 A
Current (I _{th}):	
Conventional Thermal Current	Fully Enclosed 25 A
(I _{the}):	

25 A
4 kV
690 V
690 V
for 1 s 0.3 kiloampere rms
1.8 W
3
Key operated
ON - OFF switch: 0-position: 9 o´clock, step angle 90°, front plate 0-1
Black
Snap-on door mounting
3
3
Screw Terminals
600 V AC 25 A
Document Number)
1SCC302005D0201
1SCC302013F0006
1SCC302013F0006
1SCC302013F0006
1SCC302013F0006 1 piece
1 piece
1 piece 70 mm
1 piece 70 mm 122 mm
1 piece 70 mm 122 mm 70 mm
1 piece 70 mm 122 mm 70 mm 0.13 kg
1 piece 70 mm 122 mm 70 mm 0.13 kg
1 piece 70 mm 122 mm 70 mm 0.13 kg 6417019564142
1 piece 70 mm 122 mm 70 mm 0.13 kg 6417019564142

