

2020-09-30 All Countries

PRODUCT-DETAILS

Last Ordering Date

## OC25G04PXBN00NA4

# OC25G04PXBN00NA4 Cam switch



Extended Product Type	OC25G04PXBN00NA4
Product ID	1SCA126454R1001
EAN	6417019564241
Catalog Description	OC25G04PXBN00NA4 Cam switch
Long Description	OC25 Cam switch, Ith=25A, ON-OFF, 4-contacts, Snap-on door mounting, Black Basic handle, Round front ring. Black handle included with round front ring. The round front ring handle is used in applications where position indication or engravings is not needed on the switch

Popular Downloads	
Data Sheet, Technical Information	1SCC302009C0201
Instructions and Manuals	1SCC302013F0006
Wiring Diagram	15CC202014M0201

Dimensions	
Product Net Width	39 mm

Product Net Height	41 mm
Product Net Depth / Length	95 mm
Product Net Weight	0.11 kg

Technical	
Rated Operational Current AC-22A (I <sub>e</sub> )	(500 V) 20 A (690 V) 20 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(690 V) Three Phase 5.9 A (500 V) Three Phase 8.1 A (230 V) Three Phase 15 A (400 V) Three Phase 15 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(690 V) Three Phase 4.8 kW (500 V) Three Phase 4.8 kW (230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 25 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 25 A
Rated Continuous Thermal Current	25 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Rated Insulation Voltage (U <sub>i</sub> )	690 V
Rated Operational Voltage	690 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 0.3 kA for 3 s 0.173 kA
Power Loss	1.8 W
Pollution Degree	3
Handle Type	Basic handle, Round front ring
Special Functions	ON - OFF switch: 0-position: 9 o´clock, step angle 90°, front plate 0-1
Color	Black
Mounting Type	Snap-on door mounting
Number of Contacts	4
Number of Poles	4
Enclosure Type	Not enclosed
Terminal Type	Screw Terminals

### Technical UL/CSA

Ampere Rating UL/CSA 600 V AC 25 A

## **Certificates and Declarations (Document Number)**

Declaration of	1SCC302005D0201
Conformity - CE	
Instructions and	1SCC302013F0006
Manuals	

#### **Container Information**

Package Level 1 Units	1 piece
Package Level 1 Width	70 mm
Package Level 1 Depth /	122 mm

OC25G04PXBN00NA4

3

#### Length

Package Level 1 Height	70 mm
Package Level 1 Gross Weight	0.11 kg
Package Level 1 EAN	6417019564241

Classifications	
Object Classification Code	Q
ETIM 5	EC002611 - Control switch
ETIM 6	EC002611 - Control switch
ETIM 7	EC002611 - Control switch
UNSPSC	39122217
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

### Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Cam Switches

