

51 mm

PRODUCT-DETAILS

**Product Net Width** 

# OC25G06PNBN00NA6

# OC25G06PNBN00NA6 Cam switch



Extended Product Type	OC25G06PNBN00NA6
Product ID	1SCA126459R1001
EAN	6417019564302
Catalog Description	OC25G06PNBN00NA6 Cam switch
Long Description	OC25 Cam switch, Ith=25A, ON-OFF, 6-contacts, Snap-on door mounting, Black Basic handle. Black handle and frontplate with standard text are included. Special engraved frontplates to be ordered as separate items.
Ordoring	
Ordering	
Ordering  Last Ordering Date	2020-09-30 All Countries
Last Ordering Date	2020-09-30 All Countries
	2020-09-30 All Countries
Last Ordering Date	
Last Ordering Date  Popular Downloads  Data Sheet, Technical	1SCC302009C0201
Popular Downloads  Data Sheet, Technical Information Instructions and	1SCC302014M0201

2

Product Net Height	51 mm
Product Net Depth / Length	107 mm
Product Net Weight	0.13 kg

Technical	
Rated Operational Current AC-22A (I <sub>e</sub> )	(500 V) 20 A (690 V) 20 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(690 V) Three Phase 5.9 A (500 V) Three Phase 8.1 A (230 V) Three Phase 15 A (400 V) Three Phase 15 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(690 V) Three Phase 4.8 kW (500 V) Three Phase 4.8 kW (230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW
Conventional Free-air Thermal Current (I <sub>th</sub> )	q = 40 °C 25 A
Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 25 A
Rated Continuous Thermal Current	25 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Rated Insulation Voltage (U <sub>i</sub> )	690 V
Rated Operational Voltage	690 V
Rated Short-time Withstand Current (I <sub>cw</sub> )	for 1 s 0.3 kA for 3 s 0.173 kA
Power Loss	1.8 W
Pollution Degree	3
Handle Type	Basic handle
Special Functions	ON - OFF switch: 0-position: 9 o´clock, step angle 90°, front plate 0-1
Color	Black
Mounting Type	Snap-on door mounting
Number of Contacts	6
Number of Poles	6
Enclosure Type	Not enclosed
Terminal Type	Screw Terminals

## Technical UL/CSA

Ampere Rating UL/CSA 600 V AC 25 A

# **Certificates and Declarations (Document Number)**

Declaration of Conformity - CE	1SCC302005D0201
Instructions and	1SCC302013F0006
Manuals	

### **Container Information**

Package Level 1 Units	1 piece
Package Level 1 Width	70 mm
Package Level 1 Depth /	122 mm

OC25G06PNBN00NA6

3

#### Length

Package Level 1 Height	70 mm	
Package Level 1 Gross Weight	0.13 kg	
Package Level 1 EAN	6417019564302	

Classifications	assifications	
Object Classification Code	Q	
ETIM 5	EC002611 - Control switch	
ETIM 6	EC002611 - Control switch	
ETIM 7	EC002611 - Control switch	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

### Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Cam Switches

