OC10G02PNBN00NA02



Products + Low Voltage Products and Systems + Switches + Cam Switches

Customs Tariff Number:	85365080
Minimum Order Quantity:	1 piece
Ordering	
Long Description:	OC10 Cam switch, Ith=10A, ON-OFF, 2-contacts, Snap-on door mounting, Black Basic handle. Black handle and frontplate with standard text are incl uded. Special engraved frontplates to be ordered as separate items.
Catalog Description:	OC10G02PNBN00NA02 Cam switch
EAN:	6417019564388
Product ID:	1SCA126468R1001
Extended Product Type:	OC10G02PNBN00NA02
General Information	

Popular Downloads

Data Sheet, Technical Information:	1SCC302009C0201
Instructions and Manuals:	1SCC302013F0006
Wiring Diagram:	1SCC302014M0201

Dimensions

Product Net Width:	32 mm
Product Net Height:	32 mm
Product Net Depth:	69 mm
Product Net Weight:	0.04 kg

Technical

Rated Operational Current AC-22A	(500 V) 10 A
(I _e):	
Rated Operational Current AC-23A	(230 V) Three Phase 7.6 A
(I _e):	(400 V) Three Phase 6.5 A
Rated Operational Power AC-23A	(230 V) Three Phase 1.8 kW
(P _e):	(400 V) Three Phase 3 kW
Conventional Free-air Thermal	q = 40 °C 10 A
Current (I _{th}):	
Conventional Thermal Current	Fully Enclosed 10 A
(I _{the}):	
Rated Continuous Thermal	10 A
Current:	

Rated Impulse Withstand Voltage (U _{imp}):	2.5 kV
Rated Insulation Voltage (U _i):	500 V
Rated Operational Voltage:	500 V
Rated Short-time Withstand Current (I _{cw}):	for 1 s 0.12 kiloampere rms
Power Loss:	0.6 W
Pollution Degree:	3
Handle Type:	Basic handle
Special Functions:	ON - OFF switch: 0-position: 12 o´clock, step angle 90°, front plate 0-1
Color:	Black
Mounting Type:	Snap-on door mounting
Number of Contacts:	2
Number of Poles:	2
Terminal Type:	Screw Terminals
Technical UL/CSA	
Ampere Rating UL/CSA:	600 V AC 10 A
Certificates and Declarations (Document Number)
Declaration of Conformity - CE:	1SCC302005D0201
Instructions and Manuals:	1SCC302013F0006
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Units: Package Level 1 Width:	1 piece 50 mm
Package Level 1 Width:	50 mm
Package Level 1 Width: Package Level 1 Length:	50 mm 108 mm
Package Level 1 Width: Package Level 1 Length: Package Level 1 Height:	50 mm 108 mm 50 mm
Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight:	50 mm 108 mm 50 mm 0.04 kg
Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight: Package Level 1 EAN:	50 mm 108 mm 50 mm 0.04 kg
Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight: Package Level 1 EAN: Classifications	50 mm 108 mm 50 mm 0.04 kg 6417019564388
Package Level 1 Width: Package Level 1 Length: Package Level 1 Height: Package Level 1 Gross Weight: Package Level 1 EAN: Classifications Object Classification Code:	50 mm 108 mm 50 mm 0.04 kg 6417019564388 Q

