OC10G02KNBN00NU1



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information	
Extended Product Type:	OC10G02KNBN00NU1
Product ID:	1SCA126486R1001
EAN:	6417019564562
Catalog Description:	OC10G02KNBN00NU1 Cam switch
Long Description:	OC10 Cam switch, Ith=10A, Change-Over, 2-contacts, Snap-on door moun
	ting, Black Key operated. Black handle and frontplate with standard text ar
	e included. Special engraved frontplates to be ordered as separate items.
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080
Dopular Downloado	
Popular Downloads	
Data Sheet, Technical Information	: 1SCC302009C0201
Instructions and Manuals:	1SCC302013F0006
Wiring Diagram:	1SCC302014M0201
Dimensions	
Due due 4 Mart Mildler	
Product Net Width:	32 mm
Product Net Width: Product Net Height:	32 mm 32 mm
Product Net Height:	32 mm
Product Net Height: Product Net Depth:	32 mm 54 mm
Product Net Height: Product Net Depth: Product Net Weight: Technical	32 mm 54 mm 0.06 kg
Product Net Height: Product Net Depth: Product Net Weight:	32 mm 54 mm 0.06 kg
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (I _e):	32 mm 54 mm 0.06 kg A (500 V) 10 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-22	32 mm 54 mm 0.06 kg A (500 V) 10 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (I _e): Rated Operational Current AC-234	32 mm 54 mm 0.06 kg (500 V) 10 A (230 V) Three Phase 7.6 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (I _e): Rated Operational Current AC-234 (I _e):	32 mm 54 mm 0.06 kg (500 V) 10 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (I _e): Rated Operational Current AC-234 (I _e): Rated Operational Power AC-23A	32 mm 54 mm 0.06 kg (500 V) 10 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (I _e): Rated Operational Current AC-234 (I _e): Rated Operational Power AC-23A (P _e):	32 mm 54 mm 0.06 kg (500 V) 10 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (Ie): Rated Operational Current AC-234 (Ie): Rated Operational Power AC-23A (Pe): Conventional Free-air Thermal Current (Ith): Conventional Thermal Current	32 mm 54 mm 0.06 kg (500 V) 10 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (Ie): Rated Operational Current AC-234 (Ie): Rated Operational Power AC-23A (Pe): Conventional Free-air Thermal Current (Ith):	32 mm 54 mm 0.06 kg A (500 V) 10 A A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW q = 40 °C 10 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-224 (Ie): Rated Operational Current AC-234 (Ie): Rated Operational Power AC-23A (Pe): Conventional Free-air Thermal Current (Ith): Conventional Thermal Current	32 mm 54 mm 0.06 kg A (500 V) 10 A A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW q = 40 °C 10 A

Rated Impulse Withstand Voltage (U _{imp}):	2.5 kV
Rated Insulation Voltage (U _i):	500 V
Rated Operational Voltage:	500 V
Rated Short-time Withstand Current (I _{cw}):	for 1 s 0.12 kiloampere rms
Power Loss:	0.6 W
Pollution Degree:	3
Handle Type:	Key operated
Special Functions:	Change-over switch: With 0-position: 12 o'clock, step angle 60°, front plate 1 -0-2
Color:	Black
Mounting Type:	Snap-on door mounting
Number of Contacts:	2
Number of Poles:	1
Terminal Type:	Screw Terminals
Technical UL/CSA	
Ampere Rating UL/CSA:	600 V AC 10 A
Certificates and Declarations (I	Document Number)
Declaration of Conformity - CE:	1SCC302005D0201
Instructions and Manuals:	1SCC302013F0006
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	50 mm
Package Level 1 Length:	108 mm
Package Level 1 Height:	50 mm
Package Level 1 Gross Weight:	0.06 kg
Package Level 1 EAN:	6417019564562
Classifications	
Object Classification Code:	Q
ETIM 5:	EC002611 - Control switch
ETIM 6:	EC002611 - Control switch
ETIM 7:	EC002611 - Control switch

