OC10G04PNBN00NU2



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information	
Extended Product Type:	OC10G04PNBN00NU2
Product ID:	1SCA126488R1001
EAN:	6417019564586
Catalog Description:	OC10G04PNBN00NU2 Cam switch
Long Description:	OC10 Cam switch, Ith=10A, Change-Over, 4-contacts, Snap-on door moun ting, Black Basic handle. Black handle and frontplate with standard text are included. Special engraved frontplates to be ordered as separate items.
Ordering	
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85365080
Popular Downloads	
Data Sheet, Technical Information	1SCC302009C0201
Instructions and Manuals:	1SCC302013F0006
Wiring Diagram:	1SCC302014M0201
Dimensions	
Product Net Width:	32 mm
Product Net Width: Product Net Height:	32 mm 32 mm
Product Net Height:	32 mm
Product Net Height: Product Net Depth:	32 mm 81 mm
Product Net Height: Product Net Depth: Product Net Weight:	32 mm 81 mm 0.05 kg
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-22A	32 mm 81 mm 0.05 kg (500 V) 10 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-22A (I _e):	32 mm 81 mm 0.05 kg (500 V) 10 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-22A (I _e): Rated Operational Current AC-23A	32 mm 81 mm 0.05 kg (500 V) 10 A (230 V) Three Phase 7.6 A
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-22A (I _e): Rated Operational Current AC-23A (I _e): Rated Operational Power AC-23A	32 mm 81 mm 0.05 kg (500 V) 10 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW
Product Net Height: Product Net Depth: Product Net Weight: Technical Rated Operational Current AC-22A (Ie): Rated Operational Current AC-23A (Ie): Rated Operational Power AC-23A (Pe): Conventional Free-air Thermal	32 mm 81 mm 0.05 kg (500 V) 10 A (230 V) Three Phase 7.6 A (400 V) Three Phase 6.5 A (230 V) Three Phase 1.8 kW (400 V) Three Phase 3 kW

Rated Impulse Withstand Voltage (U _{imp}):	2.5 kV
Rated Insulation Voltage (U _i):	500 V
Rated Operational Voltage:	500 V
Rated Short-time Withstand Current (I _{cw}):	for 1 s 0.12 kiloampere rms
Power Loss:	0.6 W
Pollution Degree:	3
Handle Type:	Basic handle
Special Functions:	Change-over switch: With 0-position: 12 o'clock, step angle 60°, front plate 1 -0-2
Color:	Black
Mounting Type:	Snap-on door mounting
Number of Contacts:	4
Number of Poles:	2
Terminal Type:	Screw Terminals
Technical UL/CSA	
Ampere Rating UL/CSA:	600 V AC 10 A
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE:	1SCC302005D0201
Instructions and Manuals:	1SCC302013F0006
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	50 mm
Package Level 1 Length:	108 mm
Package Level 1 Height:	50 mm
Package Level 1 Gross Weight:	0.05 kg
Package Level 1 EAN:	6417019564586
Classifications	
Object Classification Code:	Q
ETIM 5:	EC002611 - Control switch
ETIM 6:	EC002611 - Control switch
ETIM 7:	EC002611 - Control switch

