# OC25G08RNBN00NWS4



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information

**Extended Product Type:** OC25G08RNBN00NWS4

**Product ID:** 1SCA126535R1001

EAN: 6417019565057

OC25G08RNBN00NWS4 Cam switch **Catalog Description:** 

Long Description: OC25 Cam switch, Ith=25A, Change-Over, 8-contacts, Screw and door mo

> unting, Black Basic handle. Black handle and frontplate with standard text are included. Special engraved frontplates to be ordered as separate item

s.

Ordering

**Minimum Order Quantity:** 1 piece

**Customs Tariff Number:** 85365080

Popular Downloads

**Data Sheet, Technical** 1SCC302009C0201

Information:

Instructions and Manuals: 1SCC302013F0006

Wiring Diagram: 1SCC302014M0201

**Dimensions** 

**Product Net Width:** 51 mm

**Product Net Height:** 51 mm

**Product Net Depth:** 107 mm

**Product Net Weight:** 0.23 kg

Technical

(P<sub>e</sub>):

**Rated Operational Current AC-**(500 V) 20 A

(690 V) 20 A 22A (I<sub>e</sub>):

**Rated Operational Current AC-**(690 V) Three Phase 5.9 A 23A (I<sub>e</sub>):

(500 V) Three Phase 8.1 A (230 V) Three Phase 15 A (400 V) Three Phase 15 A

Rated Operational Power AC-23A

(690 V) Three Phase 4.8 kW

(500 V) Three Phase 4.8 kW (230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW

**Conventional Free-air Thermal**  $q = 40 \, ^{\circ}C \, 25 \, A$ 

Current (Ith):

| <b>Conventional Thermal Current</b>                    | Fully Enclosed 25 A                                                     |
|--------------------------------------------------------|-------------------------------------------------------------------------|
| (I <sub>the</sub> ):                                   |                                                                         |
| Rated Continuous Thermal Current:                      | 25 A                                                                    |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ):   | 4 kV                                                                    |
| Rated Insulation Voltage (U <sub>i</sub> ):            | 690 V                                                                   |
| Rated Operational Voltage:                             | 690 V                                                                   |
| Rated Short-time Withstand Current (I <sub>cw</sub> ): | for 1 s 0.3 kiloampere rms                                              |
| Power Loss:                                            | 1.8 W                                                                   |
| Pollution Degree:                                      | 3                                                                       |
| Handle Type:                                           | Basic handle                                                            |
| Special Functions:                                     | Change-over switch: Without 0-position, step angle 60°, front plate 1-2 |
| Color:                                                 | Black                                                                   |
| Mounting Type:                                         | Screw door mounting                                                     |
| Number of Contacts:                                    | 8                                                                       |
| Number of Poles:                                       | 4                                                                       |
| Terminal Type:                                         | Screw Terminals                                                         |
| echnical UL/CSA                                        |                                                                         |
| Ampere Rating UL/CSA:                                  | 600 V AC 25 A                                                           |

### Te

## Certificates and Declarations (Document Number)

**Declaration of Conformity - CE:** 1SCC302005D0201 **Instructions and Manuals:** 1SCC302013F0006

### **Container Information**

Package Level 1 Units: 1 piece Package Level 1 Width: 70 mm Package Level 1 Length: 158 mm Package Level 1 Height: 70 mm Package Level 1 Gross Weight: 0.23 kg Package Level 1 EAN: 6417019565057

### Classifications

| Object Classification Code: | Q                         |
|-----------------------------|---------------------------|
| ETIM 5:                     | EC002611 - Control switch |
| ETIM 6:                     | EC002611 - Control switch |
| ETIM 7:                     | EC002611 - Control switch |

