OC25G04PNBN00NSO22



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information

Extended Product Type: OC25G04PNBN00NSO22

Product ID: 1SCA126559R1001

EAN: 6417019565293

Catalog Description: OC25G04PNBN00NSO22 Cam switch

Long Description: OC25 Cam switch, Ith=25A, Multi-Step, 4-contacts, Snap-on door mountin

g, Black Basic handle. Black handle and frontplate with standard text are in

cluded. Special engraved frontplates to be ordered as separate items.

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC302009C0201

Instructions and Manuals: 1SCC302013F0006

Wiring Diagram: 1SCC302014M0201

Dimensions

Product Net Width: 51 mm

Product Net Height: 51 mm

Product Net Depth: 95 mm

Product Net Weight: 0.11 kg

Technical

Rated Operational Current AC-22A

(500 V) 20 A

(l_e):

(690 V) 20 A

Rated Operational Current AC-23A

(l_e):

(690 V) Three Phase 5.9 A

(500 V) Three Phase 8.1 A (230 V) Three Phase 15 A

(400 V) Three Phase 15 A

Rated Operational Power AC-23A

(P_e):

(690 V) Three Phase 4.8 kW

(500 V) Three Phase 4.8 kW

(230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW

Conventional Free-air Thermal

Current (Ith):

 $q = 40 \, ^{\circ}C \, 25 \, A$

Conventional Thermal Current

Fully Enclosed 25 A

(I_{the}):

Rated Continuous Thermal Current:	25 A
Rated Impulse Withstand Voltage (U _{imp}):	4 kV
Rated Insulation Voltage (U _i):	690 V
Rated Operational Voltage:	690 V
Rated Short-time Withstand Current (I _{cw}):	for 1 s 0.3 kiloampere rms
Power Loss:	1.8 W
Pollution Degree:	3
Handle Type:	Basic handle
Special Functions:	Multistep switch: 2-step, with 0-position: 12 o'clock, step angle 30°, front plate 0-1-2
Color:	Black
Mounting Type:	Snap-on door mounting
Number of Contacts:	4
Number of Poles:	2
Terminal Type:	Screw Terminals

Technical UL/CSA

Ampere Rating UL/CSA: 600 V AC 25 A

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SCC302005D0201 1SCC302013F0006 **Instructions and Manuals:**

Container Information

Package Level 1 Units: 1 piece Package Level 1 Width: 70 mm Package Level 1 Length: 122 mm Package Level 1 Height: 70 mm Package Level 1 Gross Weight: 0.11 kg

Package Level 1 EAN: 6417019565293

Classifications

Object Classification Code:	Q
ETIM 5:	EC002611 - Control switch
ETIM 6:	EC002611 - Control switch
ETIM 7:	EC002611 - Control switch

