

PRODUCT-DETAILS

OC25G08PNBN00NSO24

OC25G08PNBN00NSO24 Cam switch



Extended Product Type	OC25G08PNBN00NSO24
Product ID	1SCA126563R1001
EAN	6417019565330
Catalog Description	OC25G08PNBN00NSO24 Cam switch
Long Description	OC25 Cam switch, Ith=25A, Multi-Step, 8-contacts, Snap-on door mounting, Black Basic handle. Black handle and frontplate with standard text are included. Special engraved frontplates to be ordered as separate items
Ordering	
Last Ordering Date	2020-09-30 All Countries
	2020-09-30 All Countries
Popular Downloads Data Sheet, Technical Information	2020-09-30 All Countries 1SCC302009C0201
Popular Downloads Data Sheet, Technical	
Popular Downloads Data Sheet, Technical Information Instructions and	1SCC302009C0201 1SCC302013F0006
Popular Downloads Data Sheet, Technical Information Instructions and Manuals	1SCC302009C0201

Product Net Height	51 mm
Product Net Depth / Length	119 mm
Product Net Weight	0.16 kg

Technical	
Rated Operational Current AC-22A (I _e)	(500 V) 20 A (690 V) 20 A
Rated Operational Current AC-23A (I _e)	(690 V) Three Phase 5.9 A (500 V) Three Phase 8.1 A (230 V) Three Phase 15 A (400 V) Three Phase 15 A
Rated Operational Power AC-23A (Pe)	(690 V) Three Phase 4.8 kW (500 V) Three Phase 4.8 kW (230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 25 A
Conventional Thermal Current (I _{the})	Fully Enclosed 25 A
Rated Continuous Thermal Current	25 A
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Insulation Voltage (U _i)	690 V
Rated Operational Voltage	690 V
Rated Short-time Withstand Current (I _{cw})	for 1 s 0.3 kA for 3 s 0.173 kA
Power Loss	1.8 W
Pollution Degree	3
Handle Type	Basic handle
Special Functions	Multistep switch: 2-step, with 0-position: 12 o'clock, step angle 30°, front plate 0-1-2
Color	Black
Mounting Type	Snap-on door mounting
Number of Contacts	8
Number of Poles	4
Enclosure Type	Not enclosed
Terminal Type	Screw Terminals

Technical UL/CSA

Ampere Rating UL/CSA 600 V AC 2	25 A
---------------------------------	------

Certificates	and De	clarations	(Document	Number)
CELLILICALES	allu De	ciai ativiis	(DOCUINEIIC	MULLIDEL)

Declaration of Conformity - CE	1SCC302005D0201
Instructions and	1SCC302013F0006
Manuals	

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	70 mm

Package Level 1 Depth / Length	158 mm
Package Level 1 Height	70 mm
Package Level 1 Gross Weight	0.16 kg
Package Level 1 EAN	6417019565330

Classifications	
Object Classification Code	Q
ETIM 5	EC002611 - Control switch
ETIM 6	EC002611 - Control switch
ETIM 7	EC002611 - Control switch
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems \rightarrow Switches \rightarrow Cam Switches

