OC25G09PNBN00NSO33



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information

Extended Product Type: OC25G09PNBN00NSO33

Product ID: 1SCA126573R1001

EAN: 6417019565439

OC25G09PNBN00NSO33 Cam switch **Catalog Description:**

Long Description: OC25 Cam switch, Ith=25A, Multi-Step, 9-contacts, Snap-on door mountin

g, Black Basic handle. Black handle and frontplate with standard text are in

cluded. Special engraved frontplates to be ordered as separate items.

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical

1SCC302009C0201

Information:

Instructions and Manuals: 1SCC302013F0006

Wiring Diagram: 1SCC302014M0201

Dimensions

Product Net Width: 51 mm

Product Net Height: 51 mm

Product Net Depth: 131 mm

Product Net Weight: 0.18 kg

Technical

Rated Operational Current AC-(500 V) 20 A

22A (I_e): (690 V) 20 A

Rated Operational Current AC-(690 V) Three Phase 5.9 A

23A (I_e): (500 V) Three Phase 8.1 A

(230 V) Three Phase 15 A

(400 V) Three Phase 15 A

Rated Operational Power AC-23A

(690 V) Three Phase 4.8 kW (P_e):

(500 V) Three Phase 4.8 kW (230 V) Three Phase 2.6 kW

(400 V) Three Phase 7.5 kW

Conventional Free-air Thermal

Current (Ith):

 $q = 40 \, ^{\circ}C \, 25 \, A$

| Conventional Thermal Current (I _{the}): | Fully Enclosed 25 A |
|--|---|
| Rated Continuous Thermal Current: | 25 A |
| Rated Impulse Withstand Voltage (U _{imp}): | 4 kV |
| Rated Insulation Voltage (U _i): | 690 V |
| Rated Operational Voltage: | 690 V |
| Rated Short-time Withstand Current (I _{cw}): | for 1 s 0.3 kiloampere rms |
| Power Loss: | 1.8 W |
| Pollution Degree: | 3 |
| Handle Type: | Basic handle |
| Special Functions: | Multistep switch: 3-step, with 0-position: 12 o'clock, step angle 30°, front pl ate 0-1-2-3 |
| Color: | Black |
| Mounting Type: | Snap-on door mounting |
| Number of Contacts: | 9 |
| Number of Poles: | 3 |
| Terminal Type: | Screw Terminals |
| Technical UL/CSA | |
| Ampere Rating UL/CSA: | 600 V AC 25 A |
| Certificates and Declarations (Document Number) | |
| Declaration of Conformity - CE: | 1SCC302005D0201 |
| Instructions and Manuals: | 1SCC302013F0006 |
| Container Information | |
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 70 mm |
| Package Level 1 Length: | 158 mm |
| Package Level 1 Height: | 70 mm |
| Package Level 1 Gross Weight: | 0.18 kg |
| Package Level 1 EAN: | 6417019565439 |
| Classifications | |
| E-nummer: | 3134297 |
| Object Classification Code: | Q |

EC002611 - Control switch

ETIM 5:

ETIM 6: EC002611 - Control switch

ETIM 7: EC002611 - Control switch

