OC25G06PNBN00NST32



Products + Low Voltage Products and Systems + Switches + Cam Switches

General Information

Extended Product Type: OC25G06PNBN00NST32

Product ID: 1SCA126583R1001

EAN: 6417019565538

Catalog Description: OC25G06PNBN00NST32 Cam switch

Long Description: OC25 Cam switch, Ith=25A, Multi-Step, 6-contacts, Snap-on door mountin

g, Black Basic handle. Black handle and frontplate with standard text are in

cluded. Special engraved frontplates to be ordered as separate items.

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC302009C0201

Instructions and Manuals: 1SCC302013F0006

Wiring Diagram: 1SCC302014M0201

Dimensions

Product Net Width: 51 mm

Product Net Height: 51 mm

Product Net Depth: 107 mm

Product Net Weight: 0.14 kg

Technical

Rated Operational Current AC-22A

(500 V) 20 A

(l_e):

(690 V) 20 A

Rated Operational Current AC-23A

(l_e):

(690 V) Three Phase 5.9 A

(500 V) Three Phase 8.1 A (230 V) Three Phase 15 A

(400 V) Three Phase 15 A

Rated Operational Power AC-23A

(P_e):

(690 V) Three Phase 4.8 kW

(500 V) Three Phase 4.8 kW

(230 V) Three Phase 2.6 kW (400 V) Three Phase 7.5 kW

Conventional Free-air Thermal $q = 40^{\circ}$

Current (Ith):

q = 40 °C 25 A

Conventional Thermal Current

Fully Enclosed 25 A

(I_{the}):

Rated Continuous Thermal Current: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Voltage: 690 V Rated Short-time Withstand Current (I _{cw}): Power Loss: 1.8 W Pollution Degree: 3 Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2 Terminal Type: Screw Terminals		
(U _{imp}): Rated Insulation Voltage (U _i): 690 V Rated Operational Voltage: 690 V Rated Short-time Withstand for 1 s 0.3 kiloampere rms Current (I _{cw}): Power Loss: 1.8 W Pollution Degree: 3 Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2		25 A
Rated Operational Voltage: 690 V Rated Short-time Withstand for 1 s 0.3 kiloampere rms Current (I _{cw}): Power Loss: 1.8 W Pollution Degree: 3 Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2		4 kV
Rated Short-time Withstand Current (I _{cw}): Power Loss: 1.8 W Pollution Degree: 3 Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2	Rated Insulation Voltage (U _i):	690 V
Current (I _{cw}): Power Loss: 1.8 W Pollution Degree: 3 Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2	Rated Operational Voltage:	690 V
Pollution Degree: Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2		for 1 s 0.3 kiloampere rms
Handle Type: Basic handle Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2	Power Loss:	1.8 W
Special Functions: Multistep switch: 3-step, without 0-position, step angle 30°, front plate Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2	Pollution Degree:	3
Color: Black Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2	Handle Type:	Basic handle
Mounting Type: Snap-on door mounting Number of Contacts: 6 Number of Poles: 2	Special Functions:	Multistep switch: 3-step, without 0-position, step angle 30°, front plate 1-2-3
Number of Contacts: 6 Number of Poles: 2	Color:	Black
Number of Poles: 2	Mounting Type:	Snap-on door mounting
	Number of Contacts:	6
Terminal Type: Screw Terminals	Number of Poles:	2
	Terminal Type:	Screw Terminals

Technical UL/CSA

Ampere Rating UL/CSA: 600 V AC 25 A

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SCC302005D0201

Instructions and Manuals: 1SCC302013F0006

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	70 mm
Package Level 1 Length:	122 mm
Package Level 1 Height:	70 mm
Package Level 1 Gross Weight:	0.14 kg
Package Level 1 EAN:	6417019565538

Classifications

Object Classification Code:	Q
ETIM 5:	EC002611 - Control switch
ETIM 6:	EC002611 - Control switch
ETIM 7:	EC002611 - Control switch

