OC25G06PNBN00NB6



Products + Low Voltage Products and Systems + Switches + Cam Switches

| General Information | |
|------------------------|--|
| Extended Product Type: | OC25G06PNBN00NB6 |
| Product ID: | 1SCA135006R1001 |
| EAN: | 6417019637440 |
| Catalog Description: | OC25G06PNBN00NB6 Cam switch |
| Long Description: | OC25 Cam switch, Ith=25A, ON-OFF, 6-contacts, Snap-on door mounting, Black Basic handle. Black handle and frontplate with standard text are incl uded. Special engraved frontplates to be ordered as separate items. |
| | |

Ordering

| Minimum Order Quantity: | 1 piece |
|-------------------------|----------|
| Customs Tariff Number: | 85365080 |

Popular Downloads

| Data Sheet, Technical Information: | 1SCC302009C0201 |
|------------------------------------|-----------------|
| Instructions and Manuals: | 1SCC302013F0006 |
| Wiring Diagram: | 1SCC302014M0201 |

Dimensions

| Product Net Width: | 51 mm |
|---------------------|---------|
| Product Net Height: | 51 mm |
| Product Net Depth: | 107 mm |
| Product Net Weight: | 0.13 kg |

Technical

| Rated Operational Current AC-22A (I _e): | (500 V) 20 A (690 V) 20 A |
|--|--|
| Rated Operational Current AC-23A (I _e): | (690 V) Three Phase 5.9 A (500 V) Three Phase 8.1 A |
| | (230 V) Three Phase 15 A (400 V) Three Phase 15 A |
| Rated Operational Power AC-23A | (690 V) Three Phase 4.8 kW |
| (P _e): | (500 V) Three Phase 4.8 kW |
| | (230 V) Three Phase 2.6 kW |
| | (400 V) Three Phase 7.5 kW |
| Conventional Free-air Thermal Current (I _{th}): | q = 40 °C 25 A |
| Conventional Thermal Current (I _{the}): | Fully Enclosed 25 A |

| Rated Continuous Thermal Current: | 25 A |
|---|---|
| Rated Impulse Withstand Voltage (U _{imp}): | 4 kV |
| Rated Insulation Voltage (U _i): | 690 V |
| Rated Operational Voltage: | 690 V |
| Rated Short-time Withstand Current (I _{cw}): | for 1 s 0.3 kiloampere rms |
| Power Loss: | 1.8 W |
| Pollution Degree: | 3 |
| Handle Type: | Basic handle |
| Special Functions: | ON - OFF switch: 0-position: 9 o´clock, step angle 90°, front plate 0 OFF-1 ON |
| Color: | Black |
| Mounting Type: | Snap-on door mounting |
| Number of Contacts: | 6 |
| Number of Poles: | 6 |
| Terminal Type: | Screw Terminals |
| Technical UL/CSA | |
| Ampere Rating UL/CSA: | 600 V AC 25 A |
| Certificates and Declarations (| Document Number) |
| Declaration of Conformity - CE: | 1SCC302005D0201 |
| Instructions and Manuals: | 1SCC302013F0006 |
| Container Information | |
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 70 mm |
| Package Level 1 Length: | 122 mm |
| Package Level 1 Height: | 70 mm |
| Package Level 1 Gross Weight: | 0.13 kg |
| Package Level 1 EAN: | 6417019637440 |
| Classifications | |
| Object Classification Code: | Q |
| ETIM 5: | EC002611 - Control switch |
| ETIM 6: | EC002611 - Control switch |
| ETIM 7: | EC002611 - Control switch |
| | |

