

S2C-UA 400 AC



Products → Low Voltage Products and Systems → Modular DIN Rail Products
→ Miniature Circuit Breakers MCBs Accessories → Undervoltage Releases

General Information

| | |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type: | S2C-UA 400 AC |
| Product ID: | 2CSS200911R0006 |
| EAN: | 8012542840206 |
| Catalog Description: | S2C-UA 400 AC - Undervoltage release |
| Long Description: | The S2C-UA 400 AC undervoltage release has the function to protect the load in case of a voltage drop included between 70% and 35% of its rated value. Positive safety (device tripping when the voltage is disconnected) emergency stop by means of a button. Suitable for MCBs S200 series, RCCBs F200 series and RCBOs DS201, DS202C, DS200 series. It can be used with MCBs SN201 series by means of SN201-IH interface module. Rated voltage: 400V a.c. |

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 8012542840206 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85389099 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width: | 0.018 m |
| Product Net Height: | 0.085 m |
| Product Net Depth: | 0.074 m |
| Product Net Weight: | 0.090 kg |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 0.125 m |
| Package Level 1 Height: | 0.035 m |
| Package Level 1 Length: | 0.11 m |
| Package Level 1 Gross Weight: | 0.1 kg |
| Package Level 1 EAN: | 8012542840206 |

Environmental

| | |
|---------------------|-----------------------------------|
| RoHS Status: | Following EU Directive 2011/65/EU |
|---------------------|-----------------------------------|

Additional Information

| | |
|---------------------------|--------|
| Product Main Type: | S2C-UA |
|---------------------------|--------|

| | |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Product Name: | Undervoltage release |
| Suitable For: | S200, SN201, F200, DS201, DS202C, DS200 |
| Suitable for Product Class: | Miniature Circuit Breakers MCBs Residual Current Devices RCDs Residual Current Breakers with Overload Protection RCBo |

Certificates and Declarations (Document Number)

| | |
|-------------------------------------------|---------------------|
| Data Sheet, Technical Information: | 2CSC400002D0209 |
| Declaration of Conformity - CE: | 9AKK106713A5575 |
| Environmental Information: | document not needed |
| Instructions and Manuals: | 9AKK107045A1514 |

Classifications

| | |
|------------------------------------|----------------------------------------------------------|
| ETIM 4: | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 5: | EC001286 - Auxiliary contact unit for distribution board |
| ETIM 6: | EC001286 - Auxiliary contact unit for distribution board |
| Object Classification Code: | Q |

