S2C-UA 24 DC

Products → Low Voltage Products and Systems → Modular DIN Rail Products
→ Miniature Circuit Breakers MCBs Accessories → Undervoltage Releases

General Information

Extended Product Type:	S2C-UA 24 DC
Product ID:	2CSS200911R0007
EAN:	8012542896401
Catalog Description:	S2C-UA 24 DC - Undervoltage release
Long Description:	The S2C-UA 24 DC undervoltage release has the function to protect the load in case of a voltage drop included between 70% and 35% of its rated value. Positive safety (device tripping when the voltage is disconnected) emergency stop by means of a button. Suitable for MCBs S200 series, RCCBs F200 series and RCBOs DS201, DS202C, DS200 series. It can be used with MCBs SN201 series by means of SN201-IH interface module. Rated voltage: 24V d.c.

Ordering

EAN:	8012542896401
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Width:	0.018 m
Product Net Height:	0.085 m
Product Net Depth:	0.074 m
Product Net Weight:	0.090 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.125 m
Package Level 1 Height:	0.035 m
Package Level 1 Length:	0.11 m
Package Level 1 Gross Weight:	0.1 kg
Package Level 1 EAN:	8012542896401

Environmental

RoHS Status:	Following EU Directive 2011/65/EU

Additional Information

Product Main Type:	S2C-UA

Product Name:	Undervoltage release
Suitable For:	S200, SN201, F200, DS201, DS202C, DS200
Suitable for Product Class:	Miniature Circuit Breakers MCBs Residual Current Devices RCDs Residual Current Breakers with Overload Protection RCBo

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	9AKK106713A5575
Environmental Information:	document not needed
Instructions and Manuals:	9AKK107045A1514

Classifications

ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC001286 - Auxiliary contact unit for distribution board
ETIM 6:	EC001286 - Auxiliary contact unit for distribution board
Object Classification Code:	Q