

# DDA202 AC-63/0,1



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs  
→ Residual Current Devices RCD Blocks

## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | DDA202 AC-63/0,1   |
| <b>Product ID:</b>            | 2CSB202001R2630  |
| <b>EAN:</b>                   | 8012542791607  |
| <b>Catalog Description:</b>   | DDA202 AC-63/0,1 - RCD Block   |
| <b>Long Description:</b>      | The RCD block DDA200 series is suitable for assembly with MCBs S200 series. It assures protection against the effects of sinusoidal alternating earth fault currents, protection, against indirect contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial. |

## Ordering

|                                |          |
|--------------------------------|----------|
| <b>Minimum Order Quantity:</b> | 1 piece  |
| <b>Customs Tariff Number:</b>  | 85363030 |

## Popular Downloads

|   |                 |
|---|-----------------|
| <b>Data Sheet, Technical Information:</b> | 2CSC400002D0209 |
| <b>Instructions and Manuals:</b>          | 2CSB423001D003  |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 0.070 m  |
| <b>Product Net Height:</b> | 0.093 m  |
| <b>Product Net Depth:</b>  | 0.069 m  |
| <b>Product Net Weight:</b> | 0.210 kg |

## Technical

|                                       |                     |
|---------------------------------------|---------------------|
| <b>Standards:</b>                     | IEC/EN 61009 Ann. G |
| <b>Operating Characteristic:</b>      | Instantaneous       |
| <b>Type of Residual Current:</b>      | AC type             |
| <b>Rated Residual Current:</b>        | 100 mA              |
| <b>Rated Current (I<sub>n</sub>):</b> | 63 A                |
| <b>Number of Poles:</b>               | 2                   |
| <b>Power Loss:</b>                    | 5 W                 |
| <b>Rated Voltage (U<sub>r</sub>):</b> | 230/400 V           |

## Environmental

**Ambient Air Temperature:** Operation -25 ... +55 °C  
Storage -40 ... +70 °C

**RoHS Status:** Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

**Declaration of Conformity - CE:** 9AKK106713A5614

**Environmental Information:** document not needed

**Instructions and Manuals:** 2CSB423001D003

## Container Information

**Package Level 1 Units:** 1 piece

**Package Level 1 Width:** 0.077 m

**Package Level 1 Height:** 0.076 m

**Package Level 1 Length:** 0.102 m

**Package Level 1 Gross Weight:** 0.245 kg

**Package Level 1 EAN:** 8012542791614

## Classifications

**Object Classification Code:** Q

**ETIM 4:** EC002297 - Residual current circuit breaker (RCCB) module

**ETIM 5:** EC002297 - Residual current circuit breaker (RCCB) module

**ETIM 6:** EC002297 - Residual current circuit breaker (RCCB) module

**ETIM 7:** EC002297 - Residual current circuit breaker (RCCB) module

