DDA204 A-25/0,03



Products + Low Voltage Products and Systems + Modular DIN Rail Products + Residual Current Devices RCDs + Residual Current Devices RCD Blocks

General Information	
Extended Product Type:	DDA204 A-25/0,03
Product ID:	2CSB204101R1250
EAN:	8012542798002
Catalog Description:	DDA204 A-25/0,03 - RCD Block
Long Description:	The RCD block DDA200 series is suitable for assembly with MCBs S200 s eries. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, protection, against indirects contacts a nd additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
Popular Downloads	
Data Sheet, Technical Information	2CSC400002D0209
Instructions and Manuals:	2CSB423001D003
Dimensions	
Dimensions	
Product Net Width:	0.105 m
	0.105 m 0.093 m
Product Net Width:	
Product Net Width: Product Net Height:	0.093 m
Product Net Width: Product Net Height: Product Net Depth:	0.093 m 0.069 m
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight:	0.093 m 0.069 m
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical	0.093 m 0.069 m 0.173 kg
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical Standards:	0.093 m 0.069 m 0.173 kg IEC/EN 61009 Ann. G
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic:	0.093 m 0.069 m 0.173 kg IEC/EN 61009 Ann. G Instantaneous
Product Net Width:Product Net Height:Product Net Depth:Product Net Weight:TechnicalStandards:Operating Characteristic:Type of Residual Current:	0.093 m 0.069 m 0.173 kg IEC/EN 61009 Ann. G Instantaneous A type
Product Net Width:Product Net Height:Product Net Depth:Product Net Weight:TechnicalStandards:Operating Characteristic:Type of Residual Current:Rated Residual Current:	0.093 m 0.069 m 0.173 kg IEC/EN 61009 Ann. G Instantaneous A type 30 mA
Product Net Width:Product Net Height:Product Net Depth:Product Net Weight:TechnicalStandards:Operating Characteristic:Type of Residual Current:Rated Residual Current:Rated Current (In):	0.093 m 0.069 m 0.173 kg IEC/EN 61009 Ann. G Instantaneous A type 30 mA 25 A

Environmental

Ambient Air Temperature:	Operation -25 +55 °C
	Storage -40 +70 °C
	Storage -+0 +70 C
RoHS Status:	Following EU Directive 2011/65/EU
Certificates and Declarations (I	Document Number)
Declaration of Conformity - CE:	9AKK106713A5614
Environmental Information:	document not needed
Instructions and Manuals:	2CSB423001D003
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.102 m
Package Level 1 Height:	0.075 m
Package Level 1 Length:	0.117 m
Package Level 1 Gross Weight:	0.22 kg
Package Level 1 EAN:	8012542798019
Classifications	

Classifications

Object Classification Code:	Q
ETIM 4:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 6:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 7:	EC002297 - Residual current circuit breaker (RCCB) module

