

Products → Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

## General Information

<b>Extended Product Type:</b>	B6-22-00-P-80
<b>Product ID:</b>	GJL1211509R8000
<b>EAN:</b>	4013614185397
<b>Catalog Description:</b>	B6-22-00-P-80 Mini Contactor 220-240V 40-450Hz
<b>Long Description:</b>	The B6-22-00-P mini contactor is a compact 4 pole contactor with soldering pins. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Further features are the silent coil, a switch position indication and the integrated possibility for rail mounting.

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85365080

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SBC100173C0201
<b>Instructions and Manuals:</b>	2CDC102047M6801
<b>Dimension Diagram:</b>	GJL1200438F0001

## Dimensions

<b>Product Net Width:</b>	47.5 mm
<b>Product Net Height:</b>	45.5 mm
<b>Product Net Depth:</b>	51.5 mm
<b>Product Net Weight:</b>	0.17 kg

## Technical

<b>Mini Contactor Type:</b>	Mini Contactor
<b>Rated Operational Voltage:</b>	Main Circuit 12 ... 690 V AC/DC Main Circuit 690 V AC
<b>Rated Frequency (f):</b>	Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC

<b>Rated Impulse Withstand Voltage (<math>U_{imp}</math>):</b>	Auxiliary Circuit 6 kV Main Circuit 6 kV
<b>Rated Insulation Voltage (<math>U_i</math>):</b>	690 V acc. to UL/CSA 600 V
<b>Number of Main Contacts NC:</b>	2
<b>Number of Main Contacts NO:</b>	2
<b>Rated Operational Current AC-1 (<math>I_e</math>):</b>	(220 / 240 V) 40 °C 12 A (220 / 240 V) 55 °C 12 A (380 / 440 V) 40 °C 12 A (380 / 440 V) 55 °C 12 A (690 V) 40 °C 6 A (690 V) 55 °C 6 A
<b>Rated Operational Power AC-3 (<math>P_e</math>):</b>	(220 / 230 / 240 V) 2.2 kW (400 V) 4 kW (400 V) Three Phase 4 kW (440 V) 4 kW (500 V) 4 kW (690 V) 3 kW
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 64 A
<b>Number of Auxiliary Contacts NC:</b>	0
<b>Number of Auxiliary Contacts NO:</b>	0
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	Main Circuit 12 A
<b>Rated Control Circuit Voltage (<math>U_c</math>):</b>	220 ... 240 V AC
<b>Coil Operating Limits:</b>	(acc. to IEC 60947-4-1) for AC supply 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55$ °C)
<b>Degree of Protection:</b>	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 Main Circuit Terminals IP20
<b>Mechanical Durability:</b>	10000000 cycle
<b>Maximum Electrical Switching Frequency:</b>	AC-1 300 cycles per hour AC-15 360 cycles per hour AC-3 600 cycles per hour DC-1 600 cycles per hour DC-13 360 cycles per hour DC-3 600 cycles per hour
<b>Wire Stripping Length:</b>	Auxiliary Circuit 9 mm Main Circuit 9 mm
<b>Tightening Torque:</b>	Auxiliary Circuit 0.8 ... 1.1 N·m Control Circuit 0.8 ... 1.1 N·m Main Circuit 0.8 ... 1.1 N·m
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
-------------------	--

## Environmental

<b>Ambient Air Temperature:</b>	Operation -20 ... +55 °C Storage -40 ... +80 °C
---------------------------------	--

<b>Maximum Operating Altitude Permissible:</b>	2000 m
--	--------

<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	11 ms Pulse 15g
--	-----------------

<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	5g / 5 ... 150 Hz
--	-------------------

<b>RoHS Status:</b>	Following EU Directive 2011/65/EU
---------------------	-----------------------------------

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC Auxiliary Circuit 600 V AC/DC
--	--

<b>Full Load Amps Motor Use:</b>	(240 V AC) Single Phase 4.9 A (440 ... 480 V AC) Three Phase 4.8 A
----------------------------------	---

<b>Horsepower Rating UL/CSA:</b>	(208 V AC) Three Phase 1 Hp (220 ... 240 V AC) Single Phase 0.5 Hp (220 ... 240 V AC) Three Phase 2 Hp (440 ... 480 V AC) Three Phase 3 Hp (550 ... 600 V AC) Three Phase 1 Hp
----------------------------------	--

<b>General Use Rating UL/CSA:</b>	(300 V AC) 8 A
-----------------------------------	----------------

<b>Tightening Torque UL/CSA:</b>	Auxiliary Circuit 7 in·lb Control Circuit 7 in·lb Main Circuit 7 in·lb
----------------------------------	--

## Certificates and Declarations (Document Number)

<b>BV Certificate:</b>	1SAA920000-0204
------------------------	-----------------

<b>CB Certificate:</b>	1SAA938000-2002
------------------------	-----------------

<b>CCC Certificate:</b>	1SAA938001-3805
-------------------------	-----------------

<b>cUL Certificate:</b>	cUL E191658
-------------------------	-------------

<b>Declaration of Conformity - CE:</b>	1SAD938512-0001
--	-----------------

<b>DNV GL Certificate:</b>	1SAA938000-0306
----------------------------	-----------------

<b>EAC Certificate:</b>	1SAA920000-2702
-------------------------	-----------------

<b>Instructions and Manuals:</b>	2CDC102047M6801
----------------------------------	-----------------

<b>KC Certificate:</b>	1SAA938000-1501
------------------------	-----------------

<b>LR Certificate:</b>	1SAA938000-0504
------------------------	-----------------

**RMRS Certificate:** 1SAA938000-0704

**RoHS Information:** 1SAD938512-0001

## Container Information

**Package Level 1 Units:** 10 piece

**Package Level 1 Width:** 108 mm

**Package Level 1 Height:** 69 mm

**Package Level 1 Length:** 247 mm

**Package Level 1 Gross Weight:** 1.775 kg

**Package Level 1 EAN:** 4013614413575

## Classifications

**Object Classification Code:** Q

**ETIM 4:** EC000066 - Magnet contactor, AC-switching

**ETIM 5:** EC000066 - Magnet contactor, AC-switching

**ETIM 6:** EC000066 - Power contactor, AC switching

**ETIM 7:** EC000066 - Power contactor, AC switching

**eClass:** 7.0 27371003

**UNSPSC:** 39121529

## Accessories

Identifier	Description	Type	Qty	Unit Of Measure
GJL1201319R0002	CA6-11E-P Auxiliary Contact	CA6-11E-P	1	piece
GJL1201319R0003	CA6-11M-P Auxiliary Contact	CA6-11M-P	1	piece
GJL1201319R0004	CA6-11N-P Auxiliary Contact	CA6-11N-P	1	piece

