

General Information

Extended Product Type:	CC4-01
Product ID:	1SBN010111R1001
EAN:	3471523130432
Catalog Description:	CC4-01 Lagging Auxiliary Contact Block
Long Description:	CC4-01 Lagging Auxiliary Contact Block

Ordering

EAN:	3471523130432
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Weight:	0.014 kg
----------------------------	----------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	10 mm
Package Level 1 Length:	100 mm
Package Level 1 Gross Weight:	0.014 kg
Package Level 1 EAN:	3471523130432
Package Level 2 Units:	100 piece
Package Level 2 Gross Weight:	1.4 kg
Package Level 3 Units:	2400 piece
Product Packing Type:	Bag

Technical UL/CSA

Tightening Torque UL/CSA:	Auxiliary Circuit 11 in·lb
----------------------------------	----------------------------

Additional Information

Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A

Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Mounted Auxiliary Contacts:	0 NO, 1 NC
Order Multiple:	1 piece
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-15 (I_e):	(220 / 240 V) 4 A (24 / 127 V) 6 A (400 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Rated Operational Current DC-13 (I_e):	(110 V) 0.55 A / 60 A (125 V) 0.55 A / 69 A (220 V) 0.27 A / 60 A (24 V) 6 A / 144 A (250 V) 0.27 A / 68 A (400 V) 0.15 A / 60 A (48 V) 2.8 A / 134 A (500 V) 0.13 A / 65 A (600 V) 0.1 A / 60 A (72 V) 1 A / 72 A
Rated Operational Voltage:	Auxiliary Circuit 24 ... 690 V
Rated Short-time Withstand Current (I_{cw}):	for 0.1 s 140 A for 1 s 100 A
Suitable For:	AF09 AF12 AF16 AF26 AF30 AF38 AF40 AF52 AF65 AF80 AF96 NF
Terminal Type:	Screw Terminals
Tightening Torque:	Auxiliary Circuit 1.2 N·m

Wire Stripping Length:

Auxiliary Circuit 10 mm

Certificates and Declarations (Document Number)

ABS Certificate:	ABS_15-GE1349500-PDA_90682247
CB Certificate:	CB_SE-70921M1
CCC Certificate:	CCC_2011010304496319
cUL Certificate:	UL_20180227_E252354_3_1
Data Sheet, Technical Information:	1SBC100173C0201
Declaration of Conformity - CE:	1SBD250007U1000
EAC Certificate:	EAC_RU C-FR ME77 B01048
Environmental Information:	1SBD250182E1000
GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
Instructions and Manuals:	1SBC101041M6801
LR Certificate:	LRS_1300087E1
RINA Certificate:	RINA_ELE084013XG
UL Certificate:	UL_20091128-E252354-3-1
UL Listing Card:	UL_E252354

Classifications

E-number:	3211433
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC002498 - Accessories for low-voltage switch technology
ETIM 6:	EC000041 - Auxiliary contact block
Object Classification Code:	K
UNSPSC:	39121500

