

CT-MVS.23P



Products → Low Voltage Products and Systems → Control Products → Electronic Relays and Controls
→ Time Relays

General Information

Extended Product Type:	CT-MVS.23P
Product ID:	1SVR740021R2300
EAN:	4016779851626
Catalog Description:	CT-MVS.23P Time relay, multifunction 2c/o, 380-440VAC
Long Description:	The CT-MVS.23P is a multifunction electronic time relay from the CT-S timer range. It provides 10 timing functions with 10 time ranges from 0.05 s to 300 h. This time relay operates with a rated control supply voltage of 380 - 440 V AC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. A control input works with voltage-related (non-floating) triggering. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Ordering

EAN:	4016779851626
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	97 mm
Package Level 1 Length:	30 mm
Package Level 1 Height:	109 mm
Package Level 1 Gross Weight:	0.155 kg
Package Level 1 EAN:	4016779851626

Dimensions

Product Net Width:	22.5 mm
Product Net Height:	85.6 mm
Product Net Depth:	103.7 mm
Product Net Weight:	0.133 kg

Technical

Timer Relay Type:	ON-Delay OFF-Delay Impulse ON Impulse OFF Flasher with Reset, Starting with ON Flasher with Reset, Starting with OFF Pulse Former ON / OFF Function Symmetrical ON- and OFF-Delay Flasher Starting with ON or OFF Accumulative ON-Delay Star-Delta
Time Range:	0.05 s - 300 h
Rated Control Supply Voltage (U_s):	380 ... 440 V AC
Rated Frequency (f):	50 Hz 60 Hz
Output:	2 c/o (SPDT) contacts
Terminal Type:	Screwless Terminals
Rated Operational Current AC-12 (I_e):	(230 V) 4 A
Rated Operational Current AC-15 (I_e):	(230 V) 3 A
Rated Operational Current DC-12 (I_e):	(24 V) 4 A
Rated Operational Current DC-13 (I_e):	(24 V) 2 A
Minimum Switching Capacity:	12 V 10 mA
Rated Impulse Withstand Voltage (U_{imp}):	Input Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV
Rated Insulation Voltage (U_i):	Input Circuit / Output Circuit 500 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection:	Housing IP50 Terminals IP20
Overvoltage Category:	III
Pollution Degree:	3
Short-Circuit Protective Devices:	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability:	AC-12 100000 cycle
Mechanical Durability:	30000000 cycle
Connecting Capacity:	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²

Wire Stripping Length:	8 mm
Mounting Position:	Any
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards:	EN 50581 IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +85 °C
RoHS Status:	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Output Circuit 300 V AC
Contact Rating UL/CSA:	B300
Connecting Capacity UL/CSA:	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG

Certificates and Declarations (Document Number)

CB Certificate:	CB_DK-5903-M1
CCC Certificate:	CCC_2007010303255979
cULus Certificate:	cULus508_20110711-E140448A
Data Sheet, Technical Information:	2CDC111125D0201
Declaration of Conformity - CE:	1SVD981008-0001
DNV GL Certificate:	DNV_GL_TAA00000XR
EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
Environmental Information:	1SAA981016-2401
Instructions and Manuals:	1SVC730020M0000
RMRS Certificate:	RMRS_1740021250
RoHS Information:	1SVD981008-0001

Classifications

Object Classification Code:	K
E-nummer:	4033130
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
ETIM 6:	EC001439 - Timer relay
ETIM 7:	EC001439 - Timer relay

eClass:

7.0 27371790

UNSPSC:

39121519

