

CT-SDS.22S



Products → Low Voltage Products and Systems → Control Products → Electronic Relays and Controls
→ Time Relays

General Information

Extended Product Type:	CT-SDS.22S
Product ID:	1SVR730210R3300
EAN:	4016779851534
Catalog Description:	CT-SDS.22S Time relay, star-delta 2n/o, 24-48VDC, 24-240VAC
Long Description:	The CT-SDS.22S is a single-function electronic time relay from the CT-S timer range. It provides a star-delta function with 7 time ranges from 0.05 s to 10 min. and a fixed transition time of 50 ms. This time relay operates with a rated control supply voltage of 24 - 48 V DC / 24 - 240 V AC and has a 2 n/o output with contacts rated at 250 V / 4 A. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

Ordering

EAN:	4016779851534
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	97 mm
Package Level 1 Length:	30 mm
Package Level 1 Height:	109 mm
Package Level 1 Gross Weight:	0.136 kg
Package Level 1 EAN:	4016779851534

Dimensions

Product Net Width:	22.5 mm
Product Net Height:	85.6 mm
Product Net Depth:	103.7 mm
Product Net Weight:	0.114 kg

Technical

Timer Relay Type:	Star-Delta
Time Range:	0.05 s - 10 min

Rated Control Supply Voltage (U_s):	24 ... 240 V AC 24 ... 48 V DC
Rated Frequency (f):	50 Hz 60 Hz DC Hz
Output:	2 n/o contacts
Terminal Type:	Screw Terminals
Rated Operational Current AC-12 (I_e):	(230 V) 4 A
Rated Operational Current AC-15 (I_e):	(230 V) 3 A
Rated Operational Current DC-12 (I_e):	(24 V) 4 A
Rated Operational Current DC-13 (I_e):	(24 V) 2 A
Minimum Switching Capacity:	12 V 10 mA
Rated Impulse Withstand Voltage (U_{imp}):	Input Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV
Rated Insulation Voltage (U_i):	Input Circuit / Output Circuit 500 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection:	Housing IP50 Terminals IP20
Overvoltage Category:	III
Pollution Degree:	3
Short-Circuit Protective Devices:	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability:	AC-12 100000 cycle
Mechanical Durability:	30000000 cycle
Connecting Capacity:	Flexible with Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²
Tightening Torque:	0.6 ... 0.8 N·m
Wire Stripping Length:	8 mm
Mounting Position:	Any
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Standards:	EN 50581 IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14
-------------------	---

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +85 °C
---------------------------------	--

RoHS Status:	Following EU Directive 2011/65/EU
---------------------	-----------------------------------

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Output Circuit 300 V AC
--	-------------------------

Contact Rating UL/CSA:	B300
-------------------------------	------

Connecting Capacity UL/CSA:	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
------------------------------------	--

Tightening Torque UL/CSA:	7.08 in·lb
----------------------------------	------------

Certificates and Declarations (Document Number)

CB Certificate:	CB_DK-5903-M1
------------------------	---------------

CCC Certificate:	CCC_2007010303255979
-------------------------	----------------------

cULus Certificate:	cULus508_20110711-E140448A
---------------------------	----------------------------

Data Sheet, Technical Information:	2CDC111127D0201
---	-----------------

Declaration of Conformity - CE:	1SVD981008-0001
--	-----------------

DNV GL Certificate:	DNV_GL_TAA00000XR
----------------------------	-------------------

EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
-------------------------	--------------------------

Environmental Information:	1SAA981016-2401
-----------------------------------	-----------------

Instructions and Manuals:	1SVC730020M0000
----------------------------------	-----------------

RMRS Certificate:	RMRS_1740021250
--------------------------	-----------------

RoHS Information:	1SVD981008-0001
--------------------------	-----------------

Classifications

Object Classification Code:	K
------------------------------------	---

E-number:	4033123
------------------	---------

ETIM 4:	EC001439 - Timer relay
----------------	------------------------

ETIM 5:	EC001439 - Timer relay
----------------	------------------------

ETIM 6:	EC001439 - Timer relay
----------------	------------------------

ETIM 7:	EC001439 - Timer relay
----------------	------------------------

eClass:	7.0 27371790
----------------	--------------

UNSPSC:

39121519

