

# DS202C M B25 APR30



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs  
→ Residual Current Circuit Breakers with Overcurrent Protection RCBO

## General Information

<b>Extended Product Type:</b>	DS202C M B25 APR30
<b>Product ID:</b>	2CSR272440R1255
<b>EAN:</b>	8012542121459
<b>Catalog Description:</b>	DS202C M B25 APR30 - RCBO
<b>Long Description:</b>	The DS202C series RCBO is a 2P in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; provides an optimal trade-off between safety and continuity of service, thanks to the resistance to unwanted trippings; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA); protection and isolation of resistive and inductive loads.

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85363030

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	2CSC400002D0209
<b>Instructions and Manuals:</b>	9AKK106354A0766

## Dimensions

<b>Product Net Width:</b>	0.035 m
<b>Product Net Height:</b>	0.085 m
<b>Product Net Depth:</b>	0.069 m
<b>Product Net Weight:</b>	0.239 kg

## Technical

<b>Standards:</b>	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
-------------------	--

<b>Type of Residual Current:</b>	A type
----------------------------------	--------

<b>Rated Residual Current:</b>	30 mA
--------------------------------	-------

<b>Tripping Characteristic:</b>	B
---------------------------------	---

<b>Rated Current (I<sub>n</sub>):</b>	25 A
---------------------------------------	------

<b>Number of Poles:</b>	2
-------------------------	---

<b>Number of Protected Poles:</b>	2
-----------------------------------	---

**Rated Short-Circuit Capacity (I<sub>cn</sub>):** (230 / 400 V AC) 10 kA

---

**Power Loss:** 5.5 W

---

**Rated Voltage (U<sub>r</sub>):** 230-240 V AC

---

## Environmental

**Ambient Air Temperature:** Operation -25 ... +55 °C  
Storage -40 ... +70 °C

---

**RoHS Status:** Following EU Directive 2011/65/EU

---

## Certificates and Declarations (Document Number)

**Declaration of Conformity - CE:** 9AKK106713A5589

---

**Environmental Information:** refer to RoHS information

---

**Instructions and Manuals:** 9AKK106354A0766

---

**RoHS Information:** 2CSC422002K2701

---

## Container Information

**Package Level 1 Units:** 5 piece

---

**Package Level 1 Width:** 0.253 m

---

**Package Level 1 Height:** 0.088 m

---

**Package Level 1 Length:** 0.108 m

---

**Package Level 1 Gross Weight:** 1.446 kg

---

**Package Level 1 EAN:** 8012542121466

---

## Classifications

**Object Classification Code:** Q

---

**ETIM 4:** EC000905 - Earth leakage circuit breaker

---

**ETIM 5:** EC000905 - Earth leakage circuit breaker

---

**ETIM 6:** EC000905 - Earth leakage circuit breaker

---

**ETIM 7:** EC000905 - Earth leakage circuit breaker

---



