

DS202C M C13 APR30



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs
→ Residual Current Circuit Breakers with Overcurrent Protection RCBO

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | DS202C M C13 APR30 |
| Product ID: | 2CSR272440R1134 |
| EAN: | 8012542121855 |
| Catalog Description: | DS202C M C13 APR30 - RCBO |
| Long Description: | The DS202C series RCBO is a 2P in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; provides an optimal trade-off between safety and continuity of service, thanks to the resistance to unwanted trippings; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA); protection and isolation of resistive and inductive loads. |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85363010 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 2CSC400002D0209 |
| Instructions and Manuals: | 9AKK106354A0766 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width: | 0.035 m |
| Product Net Height: | 0.085 m |
| Product Net Depth: | 0.069 m |
| Product Net Weight: | 0.239 kg |

Technical

| | |
|-------------------|--|
| Standards: | IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1 |
|-------------------|--|

| | |
|----------------------------------|--------|
| Type of Residual Current: | A type |
|----------------------------------|--------|

| | |
|--------------------------------|-------|
| Rated Residual Current: | 30 mA |
|--------------------------------|-------|

| | |
|---------------------------------|---|
| Tripping Characteristic: | C |
|---------------------------------|---|

| | |
|--|------|
| Rated Current (I_n): | 13 A |
|--|------|

| | |
|-------------------------|---|
| Number of Poles: | 2 |
|-------------------------|---|

| | |
|-----------------------------------|---|
| Number of Protected Poles: | 2 |
|-----------------------------------|---|

Rated Short-Circuit Capacity (I_{cn}): (230 / 400 V AC) 10 kA

Power Loss: 3.5 W

Rated Voltage (U_r): 230-240 V AC

Environmental

Ambient Air Temperature: Operation -25 ... +55 °C
Storage -40 ... +70 °C

RoHS Status: Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 9AKK106713A5589

Environmental Information: refer to RoHS information

Instructions and Manuals: 9AKK106354A0766

RoHS Information: 2CSC422002K2701

Container Information

Package Level 1 Units: 5 piece

Package Level 1 Width: 0.253 m

Package Level 1 Height: 0.088 m

Package Level 1 Length: 0.108 m

Package Level 1 Gross Weight: 1.446 kg

Package Level 1 EAN: 8012542121862

Classifications

Object Classification Code: Q

ETIM 4: EC000905 - Earth leakage circuit breaker

ETIM 5: EC000905 - Earth leakage circuit breaker

ETIM 6: EC000905 - Earth leakage circuit breaker

ETIM 7: EC000905 - Earth leakage circuit breaker



