

DS203NC C25 A30



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs
→ Residual Current Circuit Breakers with Overcurrent Protection RCBO

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | DS203NC C25 A30 |
| Product ID: | 2CSR256140R1254 |
| EAN: | 8012542768524 |
| Catalog Description: | DS203NC C25 A30 - RCBO |
| Long Description: | DS203NC is a 3P+N residual current circuit breaker with overcurrent protection (RCBO) in four modules for the protection against short-circuit currents, overload, earth fault currents, indirect contacts, additional protection against direct contacts (30 mA versions). |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85363030 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 2CSC423030B0201 |
| Instructions and Manuals: | 9AKK106713A8790 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width: | 0.071 m |
| Product Net Height: | 0.085 m |
| Product Net Depth: | 0.069 m |
| Product Net Weight: | 0.480 kg |

Technical

| | |
|---|--|
| Standards: | IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1 |
| Type of Residual Current: | A type |
| Rated Residual Current: | 30 mA |
| Tripping Characteristic: | C |
| Rated Current (I_n): | 25 A |
| Number of Poles: | 4 |
| Number of Protected Poles: | 3 |
| Rated Short-Circuit Capacity (I_{cn}): | (230 / 400 V AC) 6 kA |

| | |
|---------------------------------------|--------------|
| Position of Neutral Terminals: | Right |
| Power Loss: | 10.3 W |
| Rated Voltage (U_r): | 400-415 V AC |

Environmental

| | |
|---------------------------------|--|
| Ambient Air Temperature: | Operation -25 ... +55 °C Storage -40 ... +70 °C |
| RoHS Status: | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|--|---------------------------|
| Declaration of Conformity - CE: | 9AKK106713A5597 |
| Environmental Information: | refer to RoHS information |
| Instructions and Manuals: | 9AKK106713A8790 |
| RoHS Information: | 9AKK106713A8875 |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 0.076 m |
| Package Level 1 Height: | 0.096 m |
| Package Level 1 Length: | 0.073 m |
| Package Level 1 Gross Weight: | 0.530 kg |
| Package Level 1 EAN: | 8012542768524 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code: | Q |
| E-nummer: | 2160034 |
| ETIM 4: | EC000905 - Earth leakage circuit breaker |
| ETIM 5: | EC000905 - Earth leakage circuit breaker |
| ETIM 6: | EC000905 - Earth leakage circuit breaker |
| ETIM 7: | EC000905 - Earth leakage circuit breaker |

