## F202 B-63/0,3



Products + Low Voltage Products and Systems + Modular DIN Rail Products + Residual Current Devices RCDs + Residual Current Devices RCDs

| General Information                |   |  |
|------------------------------------|---|--|
| Extended Product Type:             | F202 B-63/0,3   |  |
| Product ID:                        | 2CSF202592R3630   |  |
| EAN:                               | 8012542372530   |  |
| Catalog Description:               | F202 B-63/0,3 Residual Current Circuit Breaker  |  |
| Long Description:                  | The RCCBs F200 series assures protection to people and installations aga<br>inst fault current to earth. A large offer for standard instantaneous and sele<br>ctive AC and A types is completed with some configurations for special app<br>lications. This product is particularly suitable for the protection against smo<br>oth d.c. earth fault currents. |  |
| Ordering                           |   |  |
| Minimum Order Quantity:            | 1 piece   |  |
| Customs Tariff Number:             | 85363030  |  |
| Popular Downloads                  |   |  |
| Data Sheet, Technical Information: | 2CSF423009D6401   |  |
| Instructions and Manuals:          | 9AKK106354A0846   |  |
| Dimensions                         |   |  |
| Product Net Width:                 | 0.035 m   |  |
| Product Net Height:                | 0.085 m   |  |
| Product Net Depth:                 | 0.069 m   |  |
| Product Net Weight:                | 0.500 kg  |  |
| Technical                          |   |  |
| Standards:                         | IEC/EN 61008  |  |
| Operating Characteristic:          | Instantaneous   |  |
| Type of Residual Current:          | B type  |  |
| Rated Residual Current:            | 300 mA  |  |
| Rated Current (I <sub>n</sub> ):   | 63 A  |  |

Power Loss: at Rated Operating Conditions per Pole 4.22 W

2

## Environmental

Number of Poles:

| Ambient Air Temperature: | Operation -25 +55 °C |
|--------------------------|----------------------|
|                          | Storage -40 +70 °C   |

| RoHS Status:                    | Following EU Directive 2011/65/EU |
|---------------------------------|-----------------------------------|
| Certificates and Declarations ( | (Document Number)                 |
| Declaration of Conformity - CE: | 9AKK106713A5610                   |
| Environmental Information:      | S-P-00081                         |
| Instructions and Manuals:       | 9AKK106354A0846                   |
| Container Information           |                                   |
| Package Level 1 Units:          | 1 piece                           |
| Package Level 1 Width:          | 0.073 m                           |
| Package Level 1 Height:         | 0.078 m                           |
| Package Level 1 Length:         | 0.05 m                            |
| Package Level 1 Gross Weight:   | 0.245 kg                          |
| Package Level 1 EAN:            | 8012542372530                     |

| <b>Object Classification Code:</b> | Q  |
|------------------------------------|--|
| ETIM 4:                            | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 5:                            | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 6:                            | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 7:                            | EC000003 - Residual current circuit breaker (RCCB) |

