## F202 A-63/0,03 AP-R



Products + Low Voltage Products and Systems + Modular DIN Rail Products + Residual Current Devices RCDs + Residual Current Devices RCDs

General Information	
Extended Product Type:	F202 A-63/0,03 AP-R
Product ID:	2CSF202401R1630
EAN:	8012542785309
Catalog Description:	F202 A-63/0,03 AP-R Residual Current Circuit Breaker
Long Description:	The RCCBs F200 series assures protection to people and installations aga inst fault current to earth. A large offer for standard instantaneous and sele ctive AC and A types is completed with some configurations for special app lications. This product provides the best compromise between safety and c ontinuity in the service, thanks to the resistance to unwanted trippings.
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
Popular Downloads	
Data Sheet, Technical Information:	2CSC400002D0209
Instructions and Manuals:	2CSF423001D6406
Dimensions	
Dimensions Product Net Width:	0.035 m
	0.035 m 0.085 m
Product Net Width:	
Product Net Width: Product Net Height:	0.085 m
Product Net Width: Product Net Height: Product Net Depth:	0.085 m 0.069 m
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight:	0.085 m 0.069 m
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical	0.085 m 0.069 m 0.200 kg IEC/EN 61008
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical Standards:	0.085 m 0.069 m 0.200 kg IEC/EN 61008 UL 1053
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic:	0.085 m 0.069 m 0.200 kg IEC/EN 61008 UL 1053 Instantaneous (APR High Immunity)
Product Net Width: Product Net Height: Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic: Type of Residual Current:	0.085 m         0.069 m         0.200 kg         IEC/EN 61008         UL 1053         Instantaneous (APR High Immunity)         A type
Product Net Width:Product Net Height:Product Net Depth:Product Net Weight:TechnicalStandards:Operating Characteristic:Type of Residual Current:Rated Residual Current:	0.085 m 0.069 m 0.200 kg IEC/EN 61008 UL 1053 Instantaneous (APR High Immunity) A type 30 mA
Product Net Width:Product Net Height:Product Net Depth:Product Net Weight:TechnicalStandards:Operating Characteristic:Type of Residual Current:Rated Residual Current:Rated Current (In):	0.085 m         0.069 m         0.200 kg         IEC/EN 61008         UL 1053         Instantaneous (APR High Immunity)         A type         30 mA         63 A

## Environmental

Ambient Air Temperature:	Operation -25 +55 °C
	Storage -40 +70 °C
RoHS Status:	Following EU Directive 2011/65/EU
Technical UL/CSA	
Maximum Operating Voltage UL/CSA:	277 V AC
Certificates and Declarations (D	ocument Number)
Declaration of Conformity - CE:	9AKK106713A5602
Environmental Information:	S-P-00080
Instructions and Manuals:	2CSF423001D6406
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.041 m
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Gross Weight:	0.225 kg
Package Level 1 EAN:	8012542785309
Classifications	

<b>Object Classification Code:</b>	Q
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 7:	EC000003 - Residual current circuit breaker (RCCB)

