F204 A-40/0,03-L



Products + Low Voltage Products and Systems + Modular DIN Rail Products + Residual Current Devices RCDs + Residual Current Devices RCDs

General Information	
Extended Product Type:	F204 A-40/0,03-L
Product ID:	2CSF204123R1400
EAN:	8012542820208
Catalog Description:	F204 A-40/0,03-L Residual Current Circuit Breaker
Long Description:	The RCCBs F200 series assures protection to people and installations aga inst fault current to earth. A large offer for standard instantaneous and sele ctive AC and A types is completed with some configurations for special app lications. This product is suitable for installations where neutral on the left i s needed.
Ordering	
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
Popular Downloads	
Data Sheet, Technical Information	2CSC400002D0209
Instructions and Manuals:	2CSF423001D6406
Dimensions	
Product Net Width:	0.070 m
Product Net Height:	0.085 m
Product Net Height: Product Net Depth:	0.085 m 0.069 m
Product Net Depth:	0.069 m
Product Net Depth: Product Net Weight:	0.069 m
Product Net Depth: Product Net Weight: Technical	0.069 m 0.360 kg
Product Net Depth: Product Net Weight: Technical Standards:	0.069 m 0.360 kg IEC/EN 61008
Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic:	0.069 m 0.360 kg IEC/EN 61008 Instantaneous
Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic: Type of Residual Current:	0.069 m 0.360 kg IEC/EN 61008 Instantaneous A type
Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic: Type of Residual Current: Rated Residual Current:	0.069 m 0.360 kg IEC/EN 61008 Instantaneous A type 30 mA
Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic: Type of Residual Current: Rated Residual Current: Rated Current (I _n):	0.069 m 0.360 kg IEC/EN 61008 Instantaneous A type 30 mA 40 A
Product Net Depth: Product Net Weight: Technical Standards: Operating Characteristic: Type of Residual Current: Rated Residual Current: Rated Current (I _n): Number of Poles:	0.069 m 0.360 kg IEC/EN 61008 Instantaneous A type 30 mA 40 A 4

Environmental

Ambient Air Temperature:	Operation -25 +55 °C Storage -40 +70 °C
RoHS Status:	Following EU Directive 2011/65/EU
Certificates and Declarations (Document Number)
Declaration of Conformity - CE:	9AKK106713A5602
Environmental Information:	S-P-00081
Instructions and Manuals:	2CSF423001D6406
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.082 m
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Gross Weight:	0.403 kg
Package Level 1 EAN:	8012542820208
Classifications	
Object Classification Code:	Q
E-nummer:	2160161
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 7:	EC000003 - Residual current circuit breaker (RCCB)

