

# F204 A-80/0,03



Products → Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs  
→ Residual Current Devices RCDs

## General Information

|                               |  |
|-------------------------------|--|
| <b>Extended Product Type:</b> | F204 A-80/0,03   |
| <b>Product ID:</b>            | 2CSF204101R1800  |
| <b>EAN:</b>                   | 8012542917809  |
| <b>Catalog Description:</b>   | F204 A-80/0,03 Residual Current Circuit Breaker  |
| <b>Long Description:</b>      | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. |

## Ordering

|                                |          |
|--------------------------------|----------|
| <b>Minimum Order Quantity:</b> | 1 piece  |
| <b>Customs Tariff Number:</b>  | 85363030 |

## Popular Downloads

|   |                 |
|---|-----------------|
| <b>Data Sheet, Technical Information:</b> | 2CSC400002D0209 |
| <b>Instructions and Manuals:</b>          | 2CSF423001D6406 |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 0.070 m  |
| <b>Product Net Height:</b> | 0.085 m  |
| <b>Product Net Depth:</b>  | 0.069 m  |
| <b>Product Net Weight:</b> | 0.380 kg |

## Technical

|                                       |  |
|---------------------------------------|--|
| <b>Standards:</b>                     | IEC/EN 61008<br>UL 1053                      |
| <b>Operating Characteristic:</b>      | Instantaneous                                |
| <b>Type of Residual Current:</b>      | A type                                       |
| <b>Rated Residual Current:</b>        | 30 mA  |
| <b>Rated Current (I<sub>n</sub>):</b> | 80 A   |
| <b>Number of Poles:</b>               | 4  |
| <b>Position of Neutral Terminals:</b> | Right  |
| <b>Power Loss:</b>                    | at Rated Operating Conditions per Pole 5.3 W |

## Environmental

**Ambient Air Temperature:** Operation -25 ... +55 °C  
Storage -40 ... +70 °C

**RoHS Status:** Following EU Directive 2011/65/EU

## Technical UL/CSA

**Maximum Operating Voltage** 480Y / 277 V AC  
**UL/CSA:**

## Certificates and Declarations (Document Number)

**Declaration of Conformity - CE:** 9AKK106713A5602

**Environmental Information:** S-P-00081

**Instructions and Manuals:** 2CSF423001D6406

## Container Information

**Package Level 1 Units:** 1 piece

**Package Level 1 Width:** 0.082 m

**Package Level 1 Height:** 0.078 m

**Package Level 1 Length:** 0.096 m

**Package Level 1 Gross Weight:** 0.423 kg

**Package Level 1 EAN:** 8012542917809

## Classifications

**Object Classification Code:** Q

**ETIM 4:** EC000003 - Residual current circuit breaker (RCCB)

**ETIM 5:** EC000003 - Residual current circuit breaker (RCCB)

**ETIM 6:** EC000003 - Residual current circuit breaker (RCCB)

**ETIM 7:** EC000003 - Residual current circuit breaker (RCCB)

