

PRODUCT-DETAILS

GAF460-10-11-68

GAF460-10-11 24-60V DC Contactor



General Information

Extended Product Type	GAF460-10-11-68
Product ID	1SFL597025R6811
EAN	7320500383995
Catalog Description	GAF460-10-11 24-60V DC Contactor
Long Description	A 3-pole Contactor suitable for DC-1 applications where all three poles must be connected in series in a 1-pole configuration up to max 1000 VDC. Operated with wide control voltage range 24-60 V, DC

Classifications

Object Classification Code	Q
ETIM 4	EC002552 - Power contactor, DC switching
ETIM 5	EC002552 - Power contactor, DC switching
ETIM 6	EC002552 - Power contactor, DC switching
ETIM 7	EC002552 - Power contactor, DC switching
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	12 kg
Package Level 1 EAN	7320500383995

Certificates and Declarations (Document Number)

CB Certificate	SEMKO_SE-66699
CCC Certificate	CQC_2012010304547008
cUL Certificate	20130517-E73397
Declaration of Conformity - CE	2CMT003517
EAC Certificate	9AKK107046A8618
Environmental Information	1SFC101066D0201
Instructions and Manuals	1SFC101045M9701
RoHS Information	2CMT003517
UL Listing Card	UL_E73397

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(1000 V DC) 650 A (440 V DC) 650 A (600 V DC) 650 A

Environmental

Ambient Air Temperature	Operation -40 ... +80 °C Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 5 K40 Shock Direction: B1 5 K40 Shock Direction: B2 5 K40 Shock Direction: C1 5 K40 Shock Direction: C2 5 K40
RoHS Status	Following EU Directive 2015/863 July 22, 2019 (RoHS 3)

Technical

Number of Main Contacts NO	1
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary	1

Contacts NC

Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40$ °C 700 A
Rated Operational Current DC-1 (I_e)	(1000 V) 3 Poles in Series, 40 °C 700 A (1000 V) 3 Poles in Series, 55 °C 600 A (1000 V) 3 Poles in Series, 70 °C 480 A (220 V) 3 Poles in Series, 40 °C 700 A (220 V) 3 Poles in Series, 55 °C 600 A (220 V) 3 Poles in Series, 70 °C 480 A (400 V) 3 Poles in Series, 40 °C 700 A (400 V) 3 Poles in Series, 55 °C 600 A (400 V) 3 Poles in Series, 70 °C 480 A (600 V) 3 Poles in Series, 40 °C 700 A (600 V) 3 Poles in Series, 55 °C 600 A (600 V) 3 Poles in Series, 70 °C 480 A
Rated Insulation Voltage (U_i)	acc. to UL/CSA 1000 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	DC Operation 24 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage DC 4 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 890 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 890 V-A Pull-in at Max. Rated Control Circuit Voltage DC 990 W
Connecting Capacity Main Circuit	Bar 47 mm Rigid Al-Cable 2x240 m ² Rigid Cu-Cable 240 m ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 Flexible with Insulated Ferrule 1x 0.75 ... 2.5 Flexible 2x0.75 ... 2.5 m ² Solid 2 x 1 ... 4 m ² Stranded 2 x 1 ... 4 m ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

Dimensions

Product Net Width	186 mm
Product Net Depth / Length	216 mm
Product Net Height	278 mm
Product Net Weight	10.6 kg

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	1SFC101045M9701

Dimension Diagram

53540919-59

Ordering

Minimum Order Quantity

1 piece

Customs Tariff Number

85364900

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

