

K6S-22Z-1.7-71



Products → Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | K6S-22Z-1.7-71 |
| Product ID: | GJH1213001R7221 |
| EAN: | 4013614231858 |
| Catalog Description: | K6S-22Z-1.7-71 Mini Contactor Relay 24VDC, 1.7W |
| Long Description: | The K6S-22Z mini contactor relay is a compact 4 pole contactor relay with screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors relays are used in residential buildings, commercial buildings and industrial applications for switching of control signals up to 3 A / 400 V (AC-15). Due to the low coil consumption, this device can be directly controlled by a PLC. Further features are the noiseless and hum-free coil, the integrated protective circuit with diodes and additional overvoltage protection, a switch position indication and the integrated possibility for rail or wall mounting. |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85365080 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SBC100173C0201 |
| Instructions and Manuals: | 2CDC102047M6801 |
| Dimension Diagram: | GJL1200436F0001 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width: | 52.5 mm |
| Product Net Height: | 57.5 mm |
| Product Net Depth: | 46.5 mm |
| Product Net Weight: | 0.175 kg |

Technical

| | |
|-----------------------------------|--|
| Number of Poles: | 4 |
| Mini Contactor Type: | Interface Mini Contactor Relay |
| Rated Operational Voltage: | Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC Auxiliary Circuit 690 V |

| | |
|--|---|
| Rated Frequency (f): | Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Control Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC |
| Rated Impulse Withstand Voltage (U_{imp}): | Auxiliary Circuit 6 kV |
| Rated Insulation Voltage (U_i): | 690 V acc. to UL/CSA 600 V |
| Number of Main Contacts NC: | 0 |
| Number of Main Contacts NO: | 0 |
| Number of Auxiliary Contacts NC: | 2 |
| Number of Auxiliary Contacts NO: | 2 |
| Rated Operational Current AC-15 (I_e): | (120 V) 4 A (220 / 240 V) 4 A (240 V) 4 A (24 V) 4 A (380 / 400 V) 3 A (500 V) 2 A |
| Rated Operational Current DC-13 (I_e): | (110 V) 0.7 A (220 / 240 V) 0.4 A (24 V) 2.5 A |
| Conventional Free-air Thermal Current (I_{th}): | Auxiliary Circuit 6 A |
| Rated Control Circuit Voltage (U_c): | 24 V DC |
| Coil Operating Limits: | (acc. to IEC 60947-4-1) for DC supply U _c Min. ... U _c Max. (at θ ≤ 55 °C) (acc. to IEC 60947-5-1) for DC supply 0.85 ... 1.1 x U _c (at θ ≤ 55 °C) |
| Degree of Protection: | Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 Main Circuit Terminals IP20 |
| Mechanical Durability: | 10000000 cycle |
| Minimum Switching Capacity: | 17 V 5 mA |
| Maximum Electrical Switching Frequency: | AC-15 600 cycles per hour DC-13 600 cycles per hour |
| Connecting Capacity Auxiliary Circuit: | Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ² |

| | |
|---|---|
| Connecting Capacity Control Circuit: | Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ² |
| Wire Stripping Length: | Auxiliary Circuit 9 mm |
| Tightening Torque: | Auxiliary Circuit 0.8 ... 1.1 N·m Control Circuit 0.8 ... 1.1 N·m |
| Mounting on DIN Rail: | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Power Loss: | at Rated Operating Conditions per Pole 2 W |
| Standards: | IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 |
| Remarks: | No CA6 or CAF6 mountable |

Environmental

| | |
|--|--|
| Ambient Air Temperature: | Operation -25 ... +55 °C Storage -40 ... +80 °C |
| Maximum Operating Altitude Permissible: | 2000 m |
| Resistance to Shock acc. to IEC 60068-2-27: | 11 ms Pulse 15g |
| Resistance to Vibrations acc. to IEC 60068-2-6: | 3g / 3 ... 150 Hz |
| RoHS Status: | Following EU Directive 2011/65/EU |

Technical UL/CSA

| | |
|--|--|
| Maximum Operating Voltage UL/CSA: | Auxiliary Circuit 600 V AC/DC |
| General Use Rating UL/CSA: | (600 V AC) 5 A |
| Contact Rating UL/CSA: | A600 |
| Connecting Capacity Auxiliary Circuit UL/CSA: | Stranded 1/2x 22-10 AWG |
| Tightening Torque UL/CSA: | Auxiliary Circuit 7 in·lb Control Circuit 7 in·lb |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| CB Certificate: | 1SAA938001-2001 |
| Declaration of Conformity - CE: | 1SAD938512-0001 |
| EAC Certificate: | 1SAA938001-2701 |
| Instructions and Manuals: | 2CDC102047M6801 |

RMRS Certificate: 1SAA938001-0704

RoHS Information: 1SAD938512-0001

Container Information

Package Level 1 Units: 10 piece

Package Level 1 Width: 115 mm

Package Level 1 Height: 54 mm

Package Level 1 Length: 280 mm

Package Level 1 Gross Weight: 1.82 kg

Package Level 1 EAN: 4013614411199

Classifications

Object Classification Code: K

ETIM 4: EC000196 - Contactor relay

ETIM 5: EC000196 - Contactor relay

ETIM 6: EC000196 - Contactor relay

ETIM 7: EC000196 - Contactor relay

eClass: 7.0 27371001

UNSPSC: 39121500

