


PRODUCT-DETAILS

ZK2.5-3P-GN

ZK2.5-3P-GN PI-Spring clamp Terminal Block - Feed-through - Green



General Information

Extended Product Type	ZK2.5-3P-GN
Product ID	1SNK705068R0000
EAN	3472597050688
Catalog Description	ZK2.5-3P-GN PI-Spring clamp Terminal Block - Feed-through - Green
Long Description	Find all the features of the ZK2.5 terminal block with the added option of distributing or branching 3 conductors.

Ordering

Color	Green
Minimum Order Quantity	50 piece
Customs Tariff Number	85369010

Popular Downloads

Data Sheet, Technical Information	1SNK162019D0201
Instructions and Manuals	1SNK160027C0201

Dimensions

Product Net Width	5.2 mm
-------------------	--------

Product Net Height	64.7 mm
Product Net Length	40.2 mm
Product Net Depth / Length	40.2 mm
Product Net Weight	7.4 g

Technical

Rated Cross-Section	2.5 mm ²
Spacing	5.2 mm
Connection Type	PI Spring
Function	Feed-through
Number of Levels	1
Connecting Capacity Main Circuit	Spring Clamp / Flexible 1x 0.22 ... 2.5 mm ² Spring Clamp / Rigid 1x 0.2 ... 4 mm ² Spring Clamp / With Insulated Ferrule 1x 0.22 ... 2.5 mm ² Spring Clamp / Without Insulated Ferrule 1x 0.22 ... 2.5 mm ² Spring Clamp / With Twin Ferrule 2x 0.22 ... 0.5 mm ²
Gauge Type	A2 / 2.3 mm Dia.
Rated Current (I _n)	Main Circuit 24 A
Rated Short-time Withstand Current (I _{cw})	for 1 s 300 A
Rated Voltage (U _r)	1000 V
Rated Impulse Withstand Voltage (U _{imp})	8000 V
Dielectric Test Voltage	2200 V
Pollution Degree	3
Power Loss	1 W
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material	Polyamide
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length	11.0 mm

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
Connecting Capacity Main Circuit UL/CSA	Spring Clamp / Rigid 1x 26 ... 12 AWG Spring Clamp / With Insulated Ferrule 1x 26 ... 14 AWG Spring Clamp / Without Insulated Ferrule 1x 26 ... 14 AWG
Connecting Capacity UL/CSA	Stranded 12 AWG
Flammability According to UL94	V-0
Short-Circuit Current Rating (SCCR)	100 kA

Environmental

Ambient Air Temperature	Operation -55 ... +110 °C Storage -55 ... +110 °C
Resistance to Vibrations acc. to IEC 60068-2-6	Compliant
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

ATEX Certificate	1SND162009A1702
BV Certificate	1SND162013A0203
CB Certificate	1SND162016A0200
CSA Certificate	1SND162014A0206
cUL Certificate	1SND162012A0204
Declaration of Conformity - CE	1SND225112U1004
DNV Certificate	1SND162023A0200
EAC Certificate	1SND161010A1100
Environmental Information	1SND220072E1002
Instructions and Manuals	1SNK160027C0201
RoHS Information	1SND230535F0201

Classifications

Object Classification Code		X
ETIM 4	EC000897 - Feed-through terminal block	
ETIM 5	EC000897 - Feed-through terminal block	
ETIM 6	EC000897 - Feed-through terminal block	

Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	68 mm
Package Level 1 Depth / Length	262 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.42 kg
Package Level 1 EAN	3472597050688
Package Level 2 Units	750 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	400 mm
Package Level 2 Height	200 mm
Package Level 2 Gross Weight	6.3 kg
Package Level 3 Units	36000 piece

Categories

Low Voltage Products and Systems → Connection Devices → Terminal Blocks → SNK Series

