

PRODUCT-DETAILS

TP2

TP2 Test Adapter for test plugs DIA 2 mm .079 in - Dark Grey



General Information

| | |
|-----------------------|--|
| Extended Product Type | TP2 |
| Product ID | 1SNK900203R0000 |
| EAN | 3472599097315 |
| Catalog Description | TP2 Test Adapter for test plugs DIA 2 mm .079 in - Dark Grey |
| Long Description | - Insulated test adapter that enables individual voltage control, - Direct plug-in solution into the jumpers channels, - Compatible with standard isolated or non isolated test plugs DIA 2 mm 0.079 in and 2.3 mm 0.090 in, - Withstand more than 10000 operations according to ABB test standards. |

Ordering

| | |
|------------------------|-----------|
| Color | Dark Grey |
| Minimum Order Quantity | 20 piece |
| Customs Tariff Number | 85369010 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SNK160036D0201 |
| Instructions and Manuals | 1SNK160027C0201 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 7.6 mm |
| Product Net Height | 7.6 mm |
| Product Net Length | 52.15 mm |
| Product Net Depth / Length | 52.2 mm |
| Product Net Weight | 1.7 g |

Technical

| | |
|---|--|
| Spacing | 7.6 mm |
| Function | Test Adapters |
| Rated Current (I_N) | Main Circuit 10 A |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 60 A |
| Rated Voltage (U_r) | 1000 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 8000 V |
| Dielectric Test Voltage | 2200 V |
| Pollution Degree | 3 |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material | Polyamide |
| Suitable For | ZDK2.5-22 ZDK4-22 ZDP2.5-11 ZDP2.5-22 ZDP2.5-D1 ZDP2.5-D2 ZDS4-22 ZDS4-22-R1 ZK10 ZK10-3P ZK10-PE ZK10-PE-3P ZK16 ZK16-3P ZK16-PE ZK16-PE-3P ZK2.5 ZK2.5-3P ZK2.5-4P ZK2.5-CH-4P ZK2.5-D1 ZK2.5-D1-PE ZK2.5-D2 ZK2.5-D2-PE ZK2.5-D-CH ZK2.5-PE ZK2.5-PE-3P ZK2. |

Technical UL/CSA

| | |
|----------------------------------|--------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
| Flammability According to UL94 | V-0 |

Environmental

| | |
|--|--|
| Ambient Air Temperature | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| Resistance to Vibrations acc. to IEC 60068-2-6 | Compliant |

RoHS Status

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 1SNK160027C0201 |
| RoHS Information | 1SND230505F0202 |

Classifications

| | |
|----------------------------|---|
| Object Classification Code | X |
|----------------------------|---|

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 20 piece |
| Package Level 1 Width | 158 mm |
| Package Level 1 Depth / Length | 243 mm |
| Package Level 1 Gross Weight | 0.034 kg |
| Package Level 1 EAN | 3472599097315 |
| Package Level 2 Units | 2000 piece |
| Package Level 2 Gross Weight | 3.4 kg |

Categories

Low Voltage Products and Systems → Connection Devices → Terminal Blocks Accessories → Test Adapters

