

PRODUCT-DETAILS

JB5-50

JB5-50 Jumper Bar - Orange



General Information

| | |
|-----------------------|--|
| Extended Product Type | JB5-50 |
| Product ID | 1SNK905350R0000 |
| EAN | 3472599097605 |
| Catalog Description | JB5-50 Jumper Bar - Orange |
| Long Description | Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV). |

Ordering

| | |
|------------------------|----------|
| Color | Orange |
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85369010 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SNK160027D0201 |
| Instructions and Manuals | 1SNK160027C0201 |

Dimensions

| | |
|-------------------|--------|
| Product Net Width | 5.2 mm |
|-------------------|--------|

| | |
|----------------------------|----------|
| Product Net Height | 257.8 mm |
| Product Net Length | 26.8 mm |
| Product Net Depth / Length | 26.8 mm |
| Product Net Weight | 36 g |

Technical

| | |
|---|---|
| Spacing | 5.2 mm |
| Function | Jumper Bars |
| Rated Current (I_n) | Main Circuit 32 A |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 480 A |
| Rated Voltage (U_r) | 1000 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 8000 V |
| Dielectric Test Voltage | 2200 V |
| Pollution Degree | 3 |
| Power Loss | 1 W |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material | Polyamide |
| Suitable For | ZDK2.5-22 ZDP2.5-11 ZDP2.5-22 ZDP2.5-D1 ZDP2.5-D2 ZDS4-22 ZK2.5 ZK2.5-3P ZK2.5-4P ZK2.5-CH-4P ZK2.5-D1 ZK2.5-D1-PE ZK2.5-D2 ZK2.5-D2-PE ZK2.5-D-CH ZK2.5-PE ZK2.5-PE-3P ZK2.5-PE-4P ZK2.5-S ZK2.5-S-4P ZK2.5-SP ZK2.5-SP-4P ZP2.5 ZP2.5-3P ZP2.5-4P ZP2.5-D1 ZP |

Technical UL/CSA

| | |
|----------------------------------|--------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
| Flammability According to UL94 | V-0 |

Environmental

| | |
|--|---|
| Ambient Air Temperature | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| Resistance to Vibrations acc. to IEC 60068-2-6 | Compliant |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Certificates and Declarations (Document Number)

| | |
|--------------------------|-----------------|
| ATEX Certificate | 1SND162004A1708 |
| CB Certificate | 1SND161017A0202 |
| Instructions and Manuals | 1SNK160027C0201 |
| RoHS Information | 1SND230499F0202 |

Classifications

| | | |
|----------------------------|---|---|
| Object Classification Code | | X |
| ETIM 4 | EC000489 - Cross-connector for terminal block | |
| ETIM 5 | EC000489 - Cross-connector for terminal block | |
| ETIM 6 | EC000489 - Cross-connector for terminal block | |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 10 piece |
| Package Level 1 Width | 50 mm |
| Package Level 1 Depth / Length | 311 mm |
| Package Level 1 Height | 50 mm |
| Package Level 1 Gross Weight | 0.36 kg |
| Package Level 1 EAN | 3472599097605 |
| Package Level 2 Units | 150 piece |
| Package Level 2 Gross Weight | 5.4 kg |
| Package Level 3 Units | 2100 piece |

Categories

Low Voltage Products and Systems → Connection Devices → Terminal Blocks Accessories → Jumper Bars

