

# KA2-2034



Products → Low Voltage Products and Systems → Control Products → Pilot Devices → Pilot Devices Accessories

## General Information

<b>Extended Product Type:</b>	KA2-2034
<b>Product ID:</b>	1SFA616921R2034
<b>EAN:</b>	7320500376454
<b>Catalog Description:</b>	KA2-2034 LED bulb
<b>Long Description:</b>	LED bulb - Blue - Rated Voltage 36 V, (AC)/DC - Rated Current 12 mA - Service Life >50 000 h

## Ordering

<b>EAN:</b>	7320500376454
<b>Minimum Order Quantity:</b>	20 piece
<b>Customs Tariff Number:</b>	85389099

## Dimensions

<b>Product Net Width:</b>	0.010 m
<b>Product Net Height:</b>	0.010 m
<b>Product Net Depth:</b>	0.025 m
<b>Product Net Weight:</b>	0.005 kg

## Container Information

<b>Package Level 1 Width:</b>	0.06 m
<b>Package Level 1 Height:</b>	0.01 m
<b>Package Level 1 Length:</b>	0.025 m
<b>Package Level 1 Gross Weight:</b>	0.005 kg

## Environmental

<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

## Additional Information

<b>Accessory Type:</b>	LED and filament bulbs
<b>Color:</b>	Blue
<b>Illumination:</b>	Illuminated
<b>Lamp Type:</b>	LED
<b>Luminance:</b>	750 millicandela
<b>Product Main Type:</b>	KA2
<b>Product Name:</b>	LED bulb

<b>Product Range:</b>	Compact and Modular range
<b>Product Type:</b>	KA
<b>Rated Current (I<sub>n</sub>):</b>	12 mA
<b>Rated Operational Voltage:</b>	36 V AC/DC
<b>RoHS Date:</b>	0609 3
<b>Service Life:</b>	>50000 hour
<b>Suitable For:</b>	CL
<b>Wave Length:</b>	470 nm

### Certificates and Declarations (Document Number)

<b>Data Sheet, Technical Information:</b>	1SFC151005C0201
<b>Environmental Information:</b>	1SFC151005D0201
<b>Instructions and Manuals:</b>	1SFC151005C0201
<b>RoHS Information:</b>	1SFC151017D0202

### Classifications

<b>ETIM 4:</b>	EC002024 - Accessories for control circuit devices
<b>ETIM 5:</b>	EC002024 - Accessories for control circuit devices
<b>ETIM 6:</b>	EC001019 - Single LED
<b>Object Classification Code:</b>	E
<b>UNSPSC:</b>	39120000

