

KC6-40E-F-04



Products → Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | KC6-40E-F-04 |
| Product ID: | GJH1213003R0404 |
| EAN: | 4013614130038 |
| Catalog Description: | KC6-40E-F-04 Mini Contactor Relay 110-125VDC |
| Long Description: | The KC6-40E-F mini contactor relay is a compact 4 pole contactor relay with flat pin connection. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors relays are used in residential buildings, commercial buildings and industrial applications for switching of control signals up to 3 A / 400 V (AC-15). Further features are the noiseless and hum-free coil and a switch position indication. |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85365080 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SBC100173C0201 |
| Instructions and Manuals: | 2CDC102047M6801 |
| Dimension Diagram: | GJL1200437F0001 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width: | 52.5 mm |
| Product Net Height: | 57.5 mm |
| Product Net Depth: | 46.5 mm |
| Product Net Weight: | 0.17 kg |

Technical

| | |
|-----------------------------------|--|
| Number of Poles: | 4 |
| Mini Contactor Type: | Mini Contactor Relay |
| Rated Operational Voltage: | Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC Auxiliary Circuit 690 V |

| | |
|--|---|
| Rated Frequency (f): | Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Control Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC |
| Rated Impulse Withstand Voltage (U_{imp}): | Auxiliary Circuit 6 kV |
| Rated Insulation Voltage (U_i): | 690 V acc. to UL/CSA 600 V |
| Number of Main Contacts NC: | 0 |
| Number of Main Contacts NO: | 0 |
| Number of Auxiliary Contacts NC: | 0 |
| Number of Auxiliary Contacts NO: | 4 |
| Rated Operational Current AC-15 (I_e): | (120 V) 4 A (220 / 240 V) 4 A (240 V) 4 A (24 V) 4 A (380 / 400 V) 3 A (500 V) 2 A |
| Rated Operational Current DC-13 (I_e): | (110 V) 0.7 A (220 / 240 V) 0.4 A (24 V) 2.5 A |
| Conventional Free-air Thermal Current (I_{th}): | Auxiliary Circuit 6 A |
| Rated Control Circuit Voltage (U_c): | 110 ... 125 V DC |
| Coil Operating Limits: | (acc. to IEC 60947-5-1) for DC supply 0.85 ... 1.1 x U _c (at θ ≤ 55 °C) |
| Degree of Protection: | Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 |
| Mechanical Durability: | 10000000 cycle |
| Minimum Switching Capacity: | 17 V 5 mA |
| Maximum Electrical Switching Frequency: | AC-15 600 cycles per hour DC-13 600 cycles per hour |
| Mounting on DIN Rail: | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Power Loss: | at Rated Operating Conditions per Pole 2 W |
| Standards: | IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1 |

Environmental

| | |
|--|--|
| Ambient Air Temperature: | Operation -25 ... +55 °C Storage -40 ... +80 °C |
| Maximum Operating Altitude Permissible: | 2000 m |
| Resistance to Shock acc. to IEC 60068-2-27: | 11 ms Pulse 15g |
| Resistance to Vibrations acc. to IEC 60068-2-6: | 3g / 3 ... 150 Hz |
| RoHS Status: | Following EU Directive 2011/65/EU |

Technical UL/CSA

| | |
|--|-------------------------------|
| Maximum Operating Voltage UL/CSA: | Auxiliary Circuit 600 V AC/DC |
| General Use Rating UL/CSA: | (600 V AC) 5 A |
| Contact Rating UL/CSA: | A600 |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| CB Certificate: | 1SAA938001-2001 |
| CCC Certificate: | 1SAA938000-3804 |
| cUR Certificate: | 1SAA938000-1901 |
| Declaration of Conformity - CE: | 1SAD938512-0001 |
| EAC Certificate: | 1SAA938001-2701 |
| Instructions and Manuals: | 2CDC102047M6801 |
| RMRS Certificate: | 1SAA938001-0704 |
| RoHS Information: | 1SAD938512-0001 |
| UR Certificate: | 1SAA938000-1801 |

Container Information

| | |
|--------------------------------------|---------------|
| Package Level 1 Units: | 10 piece |
| Package Level 1 Width: | 115 mm |
| Package Level 1 Height: | 54 mm |
| Package Level 1 Length: | 280 mm |
| Package Level 1 Gross Weight: | 1.77 kg |
| Package Level 1 EAN: | 4013614411465 |

Classifications

| | |
|------------------------------------|----------------------------|
| Object Classification Code: | K |
| ETIM 4: | EC000196 - Contactor relay |
| ETIM 5: | EC000196 - Contactor relay |

ETIM 6: EC000196 - Contactor relay

ETIM 7: EC000196 - Contactor relay

eClass: 7.0 27371001

UNSPSC: 39121500

