

SA/S4.16.5.1



Products → Low Voltage Products and Systems → Home and Building Automation → KNX → Standard Outputs
→ Switch Actuators 16/20 A

Products → Low Voltage Products and Systems → Intelligent Building Systems → ABB i-bus KNX → Output Devices

General Information

Extended Product Type:	SA/S4.16.5.1
Product ID:	2CDG110133R0011
EAN:	4016779708289
Catalog Description:	SA/S4.16.5.1 Switch Act, 4f 16/20 C-Load
Long Description:	Uses potential free contacts to switch 4 independent electrical loads via the ABB i-bus®. Manual operation and display of the switching state of the contacts. The 16/20AX, 16A-AC3 (C-load) device is especially suited for loads with high surge currents e.g. fluorescent lighting (AX) acc. EN 60669.

Ordering

EAN:	4016779708289
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85371091

Dimensions

Product Net Width:	72 mm
Product Net Height:	90 mm
Product Net Depth:	64.5 mm
Product Net Weight:	0.236 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	92 mm
Package Level 1 Height:	65 mm
Package Level 1 Length:	77 mm
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 EAN:	4016779708289

Additional Information

Degree of Protection:	IP20
Mounting Type:	DIN-rail adapter
Number of LEDs:	1
Number of Outputs:	4

Power Loss:	5.5 W
Product Main Type:	SA/S
Product Name:	Output Devices
Rated Current (I_n):	20 A
Voltage Range:	230 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CDC505083D0203 2CDC505101D0202
Declaration of Conformity - CE:	2CDK505094D2701

Classifications

eClass:	7.0 27143125
E-number:	1751105
ETIM 4:	EC001097 - Switch actuator for bus system
ETIM 5:	EC001097 - Switch actuator for bus system
ETIM 6:	EC001097 - Switch actuator for bus system
Object Classification Code:	A

