## E296-CP



Products + Low Voltage Products and Systems + Modular DIN Rail Products

+ Modular DIN Rail Components MDRCs + Modular DIN Rail Components MDRCs Accessories

General Information

Extended Product Type: E296-CP

**Product ID**: 2TAZ310003R1000 **EAN**: 7612270939473

Catalog Description: E296-CP Compensator

Long Description: Latching relays are electromagnetically operated devices. The E290 range

from ABB can be used to realise a simple, energysaving and efficient lighting control system. These devices are mainly used in rivate houses, factory premises and commercial and public buildings as well as in industrial plant s. As a rule, latching relays controlled by means of impulse buttons are installed where it is necessary for lighting to be operated from at least three different places. Each time a command is initiated (by means of an impulse button), an electrical pulse is applied to the coil of the latching relay. The coil in the device is briefly energised and activated. That short pulse to the coil leads to the mechanical latch of the internal main contacts. The internal switching mechanism enables us to achieve a safe and reliable interlock (in the same way as a ballpoint pen). Each pulse that is sent to the magnetic coil system switches the device ack to its previous position where it is held mechanically until the next control pulse is received. The devices are designed for rated currents 16 and 32A. Through the combinable accessories the

e main modules can be used in nearly all market applications.

Ordering

**EAN**: 7612270939473

Minimum Order Quantity: 10 piece

Customs Tariff Number: 85362020

**Dimensions** 

Product Net Width: 18 mm

Product Net Height: 85 mm

Product Net Length: 58 mm

Product Net Depth: 58 mm

Product Net Weight: 55 g

Container Information

Package Level 1 Units: 10 piece

Package Level 1 Width: 96 mm

Package Level 1 Height: 82 mm

Package Level 1 Length: 185 mm

Package Level 1 Gross Weight: 626 g

Package Level 1 EAN: 7612270939473

Environmental

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Connecting Capacity: Solid 1 x 1 ... 10 mm<sup>2</sup>

Flexible 2 x 2.5 mm<sup>2</sup>

Flexible with Cable End 1 x 0.75 ... 6 mm<sup>2</sup> Flexible with Cable Lug 1 x 0.75 ... 6 mm<sup>2</sup>

Product Main Type: E296

Product Name: Compensator

Rated Frequency (f): 50 Hz

Rated Operational Voltage: 250 V AC

**RoHS Date**: 20170426

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 2CCC441020C0201

**Declaration of Conformity - CE:** 2CCCC441010D0202

Environmental Information: 2CCC441012D0202

Instructions and Manuals: 2CCC441005M0801

RoHS Information: 2CCC413008D0206

Classifications

ETIM 4: EC000188 - Latching relay

ETIM 5: EC000188 - Latching relay

ETIM 6: EC002586 - Accessories for switching relay

Object Classification Code: K

