# OT125M3



Products + Low Voltage Products and Systems + Switches + Switch Disconnectors

**General Information** 

Extended Product Type: OT125M3

Product ID: 1SCA022429R9140 EAN: 6417019135410

Catalog Description: OT125M3 switch-disconnector

Long Description: 3-pole, front operated, base mounted, DIN-rail mountable switch-diconnect

or with protected clamp terminals, handle and shaft are not included, suita

ble for distribution board with 45mm slots

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: 1SCC301020C0201

Instructions and Manuals: 1SCC301058M0001

**Dimensions** 

Product Net Width: 70 mm

Product Net Height: 100 mm

Product Net Depth: 74 mm

Product Net Weight: 1 kg

**Technical** 

Rated Operational Current AC-21A (380 ... 415 V) 125 A

(l<sub>e</sub>):

Rated Operational Current AC-22A (380 ... 415 V) 125 A

(l<sub>e</sub>):

Rated Operational Current AC-23A (380 ... 415 V) 90 A

(l<sub>e</sub>):

Rated Operational Power AC-23A (380 ... 415 V) 45 kW

(P<sub>e</sub>):

Conventional Free-air Thermal  $q = 40 \degree C 125 A$ 

Current (Ith):

Conventional Thermal Current Fully Enclosed 125 A

(I<sub>the</sub>):

Rated Impulse Withstand Voltage 8 kV

 $(U_{imp})$ :

| Rated Insulation Voltage (U <sub>i</sub> ): | 750 V  |
|---|--|
| Rated Operational Voltage:                  | 750 V  |
| Power Loss:                                 | at Rated Operating Conditions per Pole 6.3 W |
| Pollution Degree:                           | 3  |
| Handle Type:                                | Handle and shaft not included                |
| Switches Operating Mechanism:               | Mechanism on Top of the Switch               |
| Distance Between Phases:                    | Standard                                     |
| Position of Line Terminals:                 | Top In - Bottom Out<br>Bottom In - Top Out   |
| Operating Mode:                             | Front operated                               |
| Standards:                                  | IEC 60947-3                                  |
| Special Functions:                          | No   |
| Mounting Type:                              | Base mounting                                |
| Number of Poles:                            | 3  |
| Cable Cross-Section:                        | 10 70 mm²                                    |
| Terminal Type:                              | Screw Terminals                              |
| Tightening Torque:                          | 6 N·m  |

#### Environmental

Environmental Information: 1SCC301183D0201

# Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SCC301168D2702

Environmental Information: 1SCC301183D0201

Instructions and Manuals: 1SCC301058M0001

RoHS Information: 1SCC301148D0201

## **Container Information**

Package Level 1 Units: 1 piece

Package Level 1 Width: 86 mm

Package Level 1 Length: 112 mm

Package Level 1 Height: 81 mm

Package Level 1 Gross Weight: 1 kg

Package Level 1 EAN: 6417019135410

### Classifications

E-nummer: 2102732

Object Classification Code: Q

ETIM 5: EC000216 - Switch disconnector

ETIM 6:

