

TS 25/12-24 C



Products → Low Voltage Products and Systems → Modular DIN Rail Products
→ Modular DIN Rail Components MDRCs → Transformers

General Information

Extended Product Type:	TS 25/12-24 C
Product ID:	2CSM251043R0811
EAN:	8012542928508
Catalog Description:	TS 25/12-24 C Safety isolating transformer
Long Description:	TS-C are ideal for supplying permanent power to meters, auxiliary electronic devices and circuits with very low safety voltage (SELV) for bathrooms and showers, lighting, fountains, electro-medical devices and suchlike.

Ordering

EAN:	8012542928508
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85043121

Dimensions

Product Net Width:	0.090 m
Product Net Height:	0.085 m
Product Net Depth:	0.120 m
Product Net Weight:	0.945 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.095 m
Package Level 1 Height:	0.077 m
Package Level 1 Length:	0.216 m
Package Level 1 Gross Weight:	0.92 kg
Package Level 1 EAN:	8012542928508

Technical

Power Supply:	25 V·A
Secondary Voltage:	12-24 V AC
Power Loss:	at Rated Operating Conditions per Pole 5 W

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	2CSC446003D2701
Environmental Information:	See RoHS Information
Instructions and Manuals:	On the product's body
RoHS Information:	2QD00031

Classifications

Object Classification Code:	T
E-number:	5208116
ETIM 4:	EC002048 - Current transformer
ETIM 5:	EC002048 - Current transformer
ETIM 6:	EC002048 - Current transformer
ETIM 7:	EC002048 - Current transformer

