

# CT-TGD.22



Products → Low Voltage Products and Systems → Control Products → Electronic Relays and Controls  
→ Time Relays

## General Information

<b>Extended Product Type:</b>	CT-TGD.22
<b>Product ID:</b>	1SVR500160R0100
<b>EAN:</b>	4016779657693
<b>Catalog Description:</b>	CT-TGD.22 Time relay, pulse generator 2c/o, 24-48VDC, 24-240VAC
<b>Long Description:</b>	The CT-TGD.22 is a single-function electronic time relay from the CT-D timer range. It provides a pulse generator (recycling unequal times) function with 2x7 time ranges from 0.05 s to 100 h. This time relay operates with a rated control supply voltage of 24 - 48 V DC / 24 - 240 V AC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 5 A. A control input works with voltage-related (non-floating) triggering.

## Ordering

<b>EAN:</b>	4016779657693
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85364900

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	89 mm
<b>Package Level 1 Length:</b>	20 mm
<b>Package Level 1 Height:</b>	65 mm
<b>Package Level 1 Gross Weight:</b>	0.079 kg
<b>Package Level 1 EAN:</b>	4016779657693

## Dimensions

<b>Product Net Width:</b>	17.5 mm
<b>Product Net Height:</b>	80 mm
<b>Product Net Depth:</b>	63 mm
<b>Product Net Weight:</b>	0.066 kg

## Technical

<b>Timer Relay Type:</b>	Pulse Generator
<b>Time Range:</b>	0.05 s - 100 h
<b>Rated Control Supply Voltage (U<sub>s</sub>):</b>	24 ... 240 V AC 24 ... 48 V DC

<b>Output:</b>	2 c/o (SPDT) contacts
<b>Terminal Type:</b>	Screw Terminals
<b>Rated Operational Current AC-12 (I<sub>e</sub>):</b>	(230 V) 5 A
<b>Rated Operational Current AC-15 (I<sub>e</sub>):</b>	(230 V) 3 A
<b>Rated Operational Current DC-12 (I<sub>e</sub>):</b>	(24 V) 5 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(24 V) 2 A
<b>Degree of Protection:</b>	Housing IP50 Terminals IP20
<b>Overvoltage Category:</b>	III
<b>Pollution Degree:</b>	3
<b>Short-Circuit Protective Devices:</b>	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
<b>Connecting Capacity:</b>	Flexible 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible 2x 0.5 ... 1.5 mm <sup>2</sup> Rigid 1x 0.5 ... 4 mm <sup>2</sup> Rigid 2x 0.5 ... 1.5 mm <sup>2</sup>
<b>Tightening Torque:</b>	0.5 ... 0.8 N·m
<b>Wire Stripping Length:</b>	7 mm
<b>Mounting Position:</b>	Any
<b>Mounting on DIN Rail:</b>	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
<b>Standards:</b>	EN 50581 IEC/EN 61812-1 UL 508 CAN/CSA C22.2 No.14

## Environmental

<b>Ambient Air Temperature:</b>	Operation -20 ... +60 °C Storage -40 ... +85 °C
<b>RoHS Status:</b>	Following EU Directive 2011/65/EU

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Output Circuit 300 V AC
<b>Contact Rating UL/CSA:</b>	C300
<b>Connecting Capacity UL/CSA:</b>	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-16 AWG

Tightening Torque UL/CSA: 4.43 ... 7.08 in·lb

## Certificates and Declarations (Document Number)

CCC Certificate:	CCC_2005010303153177
cUL Certificate:	cUL508_E140448
Data Sheet, Technical Information:	2CDC111158D0201
Declaration of Conformity - CE:	1SVD981010-0001
EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
Environmental Information:	1SAA981011-2402
Instructions and Manuals:	1SVC500010M1000
RMRS Certificate:	RMRS_1740021250
RoHS Information:	1SVD981010-0001
UL Certificate:	UL508_E140448

## Classifications

Object Classification Code:	K
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
ETIM 6:	EC001439 - Timer relay
ETIM 7:	EC001439 - Timer relay
eClass:	7.0 27371790
UNSPSC:	39121519

